



EFFECTIVE Q4 2019

SKU	Model Number	Product Description Long	U.S. MSRP
MTC-ThinC-EAR	MTC-ThinC-EAR	Thin-ceiling dog-ears for when ceilings (or walls) are thin. Fits C24C/CT Micro & MicroPlus, C24C/CT, C26C/CT, C19CS/CST. 1 pack contains 24 pcs of dog-ears, priced per pack.	\$ 8.00
MTC-TC	MTC-TC	Thick-ceiling dogears for ceilings up to 60 mm (2.5 in) thick. Fits C24C/CT Micro & MicroPlus, C24C/CT, C26C/CT, C19CS/CST. 1 kit (an order of "1") contains 24 pcs of dogears, priced per kit.	\$ 8.40
MTC-PC62	MTC-PC62	Terminal Cover for C62P, blk only	\$ 9.18
MTC-8124C	MTC-8124C	C-ring for 8124, for installations requiring C-ring to spread ceiling loading. Integral clips for optional MTC-Rail tile rails. (Priced as each, sold in packages of 4 pcs [for 4 speakers])	\$ 10.00
MTC-RAIL	MTC-RAIL	Tile rails for 8124, 8128 (requires MTC-8124C or MTC-8128C c-rings) or for C42C speaker (with included c-ring), (priced as each. Sold in packs of 4 pcs, for 2 spkrs).	\$ 11.00
MTC-PC60	MTC-PC60	Terminal Cover for C65, C67 P/T & C67HCT, blk only	\$ 14.00
MTC-23CM	MTC-23CM	Ceiling-Mount Adapter for Control 23, Black. Each Pack Contains 2 Pieces.	\$ 16.00
MTC-8128C	MTC-8128C	C-ring for 8128 (Priced as each, sold in packages of 4 pcs (for 4 speakers)	\$ 17.00
MTC-23CM-WH	MTC-23CM-WH	Ceiling-Mount Adapter for Control 23, White. Each Pack Contains 2 Pieces.	\$ 17.00
MTC-14WG-BK	MTC-14WG-BK	Weather Grille Accessory for Control 12C/T (Black) and 14C/T (Black). Aluminum, powder-coated, passed B117 salt-spray 200 hours, UV 100 hours, priced as each, packed in pairs. Masterpack 24 pieces.	\$ 18.00
MTC-14WG	MTC-14WG	Weather Grille Accessory for Control 12C/T (White) and 14C/T (White). Aluminum, powder-coated, passed B117 salt-spray 200 hours, UV 100 hours, priced as each, packed in pairs. Masterpack 24 pieces.	\$ 19.00
MTC-81TB8	MTC-81TB8	Tile Bridge for MTC-81BB8 backcan, 19 gauge steel with e-coating (priced as each, sold in packs of 4 pcs)	\$ 20.00
MTC-16WG	MTC-16WG	Weather Grille Accessory for Control 16C/T (White) and Control 26C & 26CT. Aluminum, powder-coated, passed B117 salt-spray 200 hours, UV 100 hours, priced as each, packed in pairs. Masterpack 24 pieces.	\$ 22.00
MTC-16WG-BK	MTC-16WG-BK	Weather Grille Accessory for Control 16C/T (Black). Aluminum, powder-coated, passed B117 salt-spray 200 hours, UV 100 hours, priced as each, packed in pairs. Masterpack 24 pieces.	\$ 22.00
CSS8004	CSS8004	4" Commercial Series Ceiling Speaker. 90 dB sens, 5W multi-tap for 100V/70V 25V, pre-assembled with driver/grille/transformer, 175 deg coverage; punched metal grille, compatible with CSS-BB4 backcan and CSS-TB4/8 tile rails (priced as each; sold individually; master packs are 6 pcs).	\$ 23.00
MTC-PC2	MTC-PC2	Sealed Panel Cover for Input Terminal Compartment. Also functions as Strain Relief. Fits all Surface-Mount Models. Gland Nut Extends Toward Back. Priced is for a package of two covers.	\$ 27.00

MTC-TB6/8	MTC-TB6/8	Tile Bridge for Medium (C227C & C227CT) and Large (C328 & C328CT) Format Ceiling Speakers. 18-Gauge steel. 25.4" x 16.3" x 1" Deep. (Price as Each, Sold 6 pcs Per Box)	\$	27.00
MTC-2P	MTC-2P	Wall-Mount Bracket Kit for Control 2P. Includes Two Wall Mounts, Not Recommended For Mobile Applications.	\$	27.24
WB6	WB6	PRE-INSTALL BRCKT C126W to studs in New Construction sold as Each priced as each	\$	27.30
WB8	WB8	Rough-In Frame for Installing Control 128W to Studs in New Construction. Sold as Each, Priced as Each.	\$	27.30
MTC-28/25CM	MTC-28/25CM	Ceiling-Mount Adapter for Control 28 and Control 25, Black. Each Pack Contains 2 Pieces.	\$	30.00
MTC-28/25CM-WH	MTC-28/25CM-WH	Ceiling-Mount Adapter for Control 28 and Control 25, White. Each Pack Contains 2 Pieces.	\$	30.00
MTC-29CM	MTC-29CM	Ceiling-Mount Adapter for Control 29AV, Black. Each Pack Contains 1 Piece.	\$	30.00
MTC-29CM-WH	MTC-29CM-WH	Ceiling-Mount Adapter for Control 29AV, White. Each Pack Contains 1 Piece.	\$	30.00
CSS8008	CSS8008	8" Commercial Series Ceiling Speaker. 96 dB sens, 5W multi-tap for 100V/70V 25V, pre-assembled with driver/grille/transformer, 120 deg coverage; punched metal grille, compatible with CSS-BB8 backcan and CSS-TB4/8 tile rails (priced as each; sold individually; master packs are 6 pcs).	\$	31.00
MTC-23UB-1	MTC-23UB-1	U-Bracket for Control 23-1 & 23-1L. Black. Priced and packaged individually. Master Pack = 6 pcs.	\$	31.00
MTC-23UB-1-WH	MTC-23UB-1-WH	MTC-23UB-1 in white.	\$	31.00
MTC-PC3	MTC-PC3	Sealed Panel Cover for Input Terminal Compartment. Also functions as Strain Relief. Fits all Surface-Mount Models. Side-Mounted Gland Nut for low-profile installations. Priced is for a package of two covers.	\$	32.00
MTC-RG6/8	MTC-RG6/8	*Previously MTC-300RG8*. Contemporary Round Grille for Control 227C/CT 6.5" and 328C/CT 8" Models". Fashionable Upscale Look, White, Metal, 13.6" Dia x 0.64" Deep. UL LISTED. Sold and Shipped as Eaches).	\$	32.00
MTC-CBT-SUS3	MTC-CBT-SUS3	Suspension Adapter Plates for ALL CBT Models Suspension Bracket, fits all CBT Models. Bent-metal adapter plates that provide convenient clip points for suspending CBT speakers via aircraft cable and other methods. Includes 2 pcs, for top & bottom mounting. Provides 3 clip points each -- center and two sides. Drilled with three speaker spacing/bolt patterns to fit: CBT-50LA-1, 100LA-1, 200LA-1, 70J-1, 70J-1+70JE-1 array, 1000, 1000+1000E array. (Priced as a carton containing 2 bent-metal adapter plates.)	\$	34.00
MTC-CBT-SUS3-WH	MTC-CBT-SUS3-WH	Suspension Adapter Plates. MTC-CBT-SUS3 in white.	\$	34.00
MTC-30CM	MTC-30CM	Ceiling-Mount Adapter for Control 30, Black. Contains 1 Piece.	\$	34.65
MTC-30CM-WH	MTC-30CM-WH	Ceiling-Mount Adapter for Control 30, White. Contains 1 Piece.	\$	34.65
HPD8124	HPD8124	4" Open-Back Ceiling Speaker. 70V/100V taps at 6W, 3W, 1.5W (plus 0.75W at 70V), high 93 dB sens, 60 Hz to 18 kHz, for non-plenum applications, 1.2 kg (2.5 lb). (Priced as each, sold in packages of 4 pcs)	\$	36.00
MTC-23WVG-1	MTC-23WVG-1	WeatherMax™ Replacement Grille for Control 23-1 for harsh environments. Thick aluminum with 3-layer foam backing and powdercoat finish, black. Provides IP-55 Grille Rating. Priced and packaged individually.	\$	37.00
MTC-23WVG-1-WH	MTC-23WVG-1-WH	MTC-23WVG-1 in white.	\$	37.00
MTC-81BB8	MTC-81BB8	Pre-Install backcan for 8138, 7.4 liter, 7"H x 11-3/4" dia, 11-1/4" mounting circle, 16 gauge steel, e-coated (priced as each sold in packs of 4 pcs)	\$	38.00

CSS-TR4/8x12	CSS-TR4/8x12	Pack of 12 pcs Tile Rails for CSS-BB4 and CSS-BB8 Backcans (Priced as package)	\$	40.00
MTC-25UB-1	MTC-25UB-1	U-Bracket for Control 25-1 & 25-1L. Black. Priced and packaged individually. Master Pack = 6 pcs.	\$	41.00
MTC-25UB-1-WH	MTC-25UB-1-WH	MTC-25UB-1 in white.	\$	41.00
MTC-25WMG	MTC-25WMG	WeatherMax™ Replacement Grille for Control 25AV & 25AV-LS only. Stainless Steel with 3-Layer Foam. Provides IP-x5 Grille Rating, Black.	\$	41.00
CSS8018	CSS8018	8" Commercial Series Ceiling Speaker. Very high 97 dB sens, 10W multi-tap for 100V/70V 25V, pre-assembled with driver/grille/transformer, 110 deg coverage; punched metal grille, compatible with CSS-BB8 backcan and CSS-TB4/8 tile rails (priced as each; sold individually; master packs are 6 pcs).	\$	42.00
MTC-CBT-FM1	MTC-CBT-FM1	"Flush-Mount" Wall Bracket for CBT50LA-1 and 100LA-1	\$	42.00
MTC-CBT-FM1-WH	MTC-CBT-FM1-WH	"Flush-Mount" Wall Bracket for CBT50LA-1 and 100LA-1, White.	\$	42.00
OSB-1	OSB-1	Overhead suspension bracket for AC895, AC195,AC266,AC299,AC566, and AC599, Blk	\$	42.00
OSB-1-WH	OSB-1-WH	Overhead suspension bracket for AC895, AC195,AC266,AC299,AC566, and AC599, White	\$	42.00
MTC-300SG12	MTC-300SG12	Contemporary Square Grille for 12" Models. Fashionable Upscale Look, White, Metal, 16.3" x 16.3" x 0.4" Deep. NOW UL LISTED	\$	43.00
HPD8128	HPD8128	8" Open-Back Ceiling Speaker. 70V/100V taps at 6W, 3W, 1.5W (plus 0.75W at 70V), very high 97 dB sens, 50 Hz to 16 kHz, for non-plenum applications, 1.4 kg (3.0 lb). (Priced as each, sold in packages of 4 pcs)	\$	47.25
229-00009-01	229-00009-01	Set of Three M10 x 35mm Forged Shoulder Steel Eyebolts (priced and ships as a PACK of 3 bolts)	\$	48.00
HPD8138	HPD8138	8" Ceiling Speaker for Pre-Install Backcan, stylish look, for use with MTC-81BB8 backcan and MTC-81TB8 tile bridge, or standard backcans. Very high 97 dB sens, 95 Hz – 18 kHz, 6W multiple tap transformer, 90° coverage. (priced as each, sold in packs of 4 pcs)	\$	50.00
IVX-802110	IVX-802110	Intellivox Cable entry cover plate 2x PG13.5, Inc. fasteners, RAL9010. Made to Order Call for availability	\$	51.00
MTC-25WMG-1	MTC-25WMG-1	WeatherMax™ Replacement Grille for Control 25-1 & 25-1L for harsh environments. Thick aluminum with 3-layer foam backing and powdercoat finish, black. Provides IP-55 Grille Rating. Priced and packaged individually.	\$	52.00
MTC-25WMG-1-WH	MTC-25WMG-1-WH	MTC-25WMG-1 in white.	\$	52.00
MTC-SG6/8	MTC-SG6/8	Contemporary Square Grille for Control 200 & 300 Series 6.5" Medium-Format and 8" Large-format Coaxial Ceiling Loudspeakers. Fashionable, upscale look, white finish over zinc-plated metal. Fits Control 227C, 227CT, 328C and 328CT.	\$	53.00
MTC-28UB-1	MTC-28UB-1	U-Bracket for Control 28-1 & 28-1L. Black. Priced and packaged individually. Master Pack = 6 pcs.	\$	53.00
MTC-28UB-1-WH	MTC-28UB-1-WH	MTC-25UB-1 in white.	\$	53.00
CSS-BB4X6	CSS-BB4X6	Pack of 6 pcs of 4" backcans for CSS8004. Steel, zinc-plated, powder-coated, 4.8" (121mm) deep, 5 knockouts (priced an sold as a pack of 6 pcs).	\$	59.00
MTC-CBT-FM2	MTC-CBT-FM2	"Flush-Mount" Wall Bracket for CBT70J-1 and 70J-1/JE-1	\$	59.00
MTC-CBT-FM2-WH	MTC-CBT-FM2-WH	"Flush-Mount" Wall Bracket for CBT70J-1 and 70J-1/JE-1, White.	\$	59.00
MTC-CBT-SMB1	MTC-CBT-SMB1	Suspension Bracket, fits all CBT Models	\$	63.00

NPATCH BLK	NPATCH BLK	Compact 2 channel analog passive volume control with Rotary volume attenuation control, Mute button; two TRS/XLR combo inputs (balanced and unbalanced); two TRS outputs (balanced and unbalanced); one Mini jack I/O. Metal enclosure. Passive design - no power required. Dimensions W x D x H: 5.1 in x 3.75 in. 2.0 in (130 mm x 95 mm x 51 mm) ; Weight: 0.8 lbs (.34 kg)	\$	69.00
CONTROL 52	CONTROL 52	Satellite Speaker, 60 mm (2.5 in) low-distortion driver, for use with C50S/T or C50CS/T subwoofer or requires external high-pass, 16 ohms, wall-mount bracket included (priced as each, sold in pairs), black.	\$	70.35
CONTROL 52-WH	CONTROL 52-WH	Satellite Speaker, 60 mm (2.5 in) low-distortion driver, for use with C50S/T or C50CS/T subwoofer or requires external high-pass, 16 ohms, wall-mount bracket included (priced as each, sold in pairs), white.	\$	70.35
MTC-28WVG-1	MTC-28WVG-1	WeatherMax™ Replacement Grille for Control 28-1 & 28-1L for harsh environments. Thick aluminum with 3-layer foam backing and powdercoat finish, black. Provides IP-55 Grille Rating. Priced and packaged individually.	\$	73.00
MTC-28WVG-1-WH	MTC-28WVG-1-WH	MTC-28WVG-1 in white.	\$	73.00
MTC-200BB6	MTC-200BB6	Backcan for Control 227C & CT. Round with extra-thick 16-gauge steel and heavy-duty 1/2" MDP reinforcement on top panel. Knockouts on sides and top panel. 0.5 cu ft, 13.3" dia x 8.1" deep, UL LISTED, (priced and shipped in eases).	\$	76.00
JBLCSR2SVBLKV	JBLCSR2SVBLKV	Wall Controller with 2-Position Source Selector and Volume Control; US Version (Black) For use with CSM-21, CSM-32	\$	80.00
JBLCSR2SVWHTV	JBLCSR2SVWHTV	Wall Controller with 2-Position Source Selector and Volume Control; US Version (White) For use with CSM-21, CSM-32	\$	80.00
JBLCSR3SVBLKV	JBLCSR3SVBLKV	Controller with 3-Position Source Selector and Volume Control; US Version (Black) For use with CSM-32	\$	80.00
JBLCSR3SVWHTV	JBLCSR3SVWHTV	Wall Controller with 3-Position Source Selector and Volume Control; US Version (White) For use with CSM-32	\$	80.00
JBLCSRVBKV	JBLCSRVBKV	Wall Controller with Volume Control; US Version (Black) For use with CSM-21, CSM-32, All CSMA	\$	80.00
JBLCSRVWHTV	JBLCSRVWHTV	Wall Controller with Volume Control; US Version (White) For use with CSM-21, CSM-32, All CSMA	\$	80.00
MTC-29UB	MTC-29UB	U-Bracket for Control 29AV.	\$	80.85
MTC-29UB-WH	MTC-29UB-WH	U-Bracket for Control 29AV, in White.	\$	80.85
MTU-15	MTU-15	U-Bracket For Model AC15, Blk	\$	82.00
MTU-15-WH	MTU-15-WH	U-Bracket For Model AC15, White	\$	82.00
CONTROL 12C/T	CONTROL 12C/T		\$	83.00
CONTROL 12C/T-BK	CONTROL 12C/T-BK	Compact Ceiling Loudspeaker with 76 mm (3 in) Full-Range Driver. 68 Hz – 17 kHz bandwidth, wide 130° coverage, 84 dB sensitivity Blind-mount backcan for quick and easy installation, dual conduit/cable clamp for in and thru cables. Combined 15 W multi-tap transformer at 70V/100V and 8Ω direct setting (20 W). Low profile backcan for shallow ceilings. Black. Sold as each, packed in pairs. International master pack is 2 speakers.	\$	83.00
CONTROL 42C	CONTROL 42C	Ultra-Compact Satellite Speaker for use with Control 40CS/T of 50S/T subwoofer, 140 Hz - 20 kHz, 82 dB sens, 30W program and 15W pink noise, 16 ohm only, 160 degree coverage, Requires external high-pass (from subwoofer crossover or electronic crossover), C-ring included, tile rails optional (priced as each, sold in pairs).	\$	84.00
IVX-802225	IVX-802225	Intellivox Wall Bracket 25mm, Set (2 pcs) Inc. fasteners, RAL9010. Made to Order Call for availability	\$	87.00
IVX-802227	IVX-802227	Intellivox Wall Bracket 25mm, Set (2 pcs) Inc. fasteners, RAL9007. Made to Order Call for availability	\$	87.00
IVX-802235	IVX-802235	Intellivox Wall Bracket 35mm, Set (2 pcs) Inc. fasteners, RAL9010. Made to Order Call for availability	\$	87.00

CONTROL 24C MICRO	CONTROL 24C MICRO	4" Two-Way Ceiling Speaker, 15W Pink Noise, 30W Program Power Capacity. 8 ohms, Shallow 4" Back Depth. For Applications with Low Ceilings. Features Extremely Wide 150° coverage. Packaged with Backcan, Grille, Support Bracket and Tile Rails. Priced as Each, Packed as Pairs. Master Pack Quantity: 8 Pieces.	\$	87.15
MTC-300T150	MTC-300T150	150 Watt Transformer for Higher Output from a 70V or 100V System. Use with Non-T Version Loudspeakers. Mounts to Tabs Inside MTC-300BB12 Back Box (Does not Mount on Driver Assembly). 3.1" H x 3.4" W x 3.4" Deep. NOW UL LISTED	\$	88.00
IVX-802005	IVX-802005	Intellivox Hinge Bracket 90°, RAL9007. Made to Order Call for availability	\$	88.00
MTC-30UB	MTC-30UB	U-Bracket for Control 30, black.	\$	88.20
MTC-30UB-WH	MTC-30UB-WH	U-Bracket for Control 30, white.	\$	88.20
WK-4S	WK-4S	CASTER SET OF 4 SWIVEL CASTERS	\$	89.00
IVX-802000	IVX-802000	Intellivox Hinge Bracket 90°, RAL9010. Made to Order Call for availability	\$	91.00
CONTROL 24CT MICRO	CONTROL 24CT MICRO	Control 24C Micro with Transformer. For use on a 70.7V or 100V Distributed Line. Taps are 8W, 4W and 2W, 1W (and 1/2W at 70.7V only). Priced as Each, Packed as Pairs. Master Pack Quantity: 8 Pieces.	\$	92.40
MTC-300BB8	MTC-300BB8	One Cubic Foot Back Box for 8" Models. Round with Extra-Thick 16 Gauge Metal and Heavy Duty ½" MDF Reinforcement on Top Panel. Knockouts on Sides and Top Panel. Fits Control 328C & 328CT. 15" Dia x 10.6" Deep. NOW UL LISTED	\$	94.00
MTC-210UB	MTC-210UB	U-Bracket for Control SB-2210 Subwoofer, Black.	\$	94.50
MTC-210UB-WH	MTC-210UB-WH	U-Bracket for Control SB-2210 Subwoofer, White	\$	94.50
CSS-H15	CSS-H15	15 Watt Paging Horn. (Priced as each, 6 in masterpack)	\$	95.00
ACTPACK	ACTPACK	Bundle that includes one Nano Patch+ compact 2 channel analog passive volume control and these accessories: 2 XLR male to XLR female Cables (3m); 2 XLR male to TRS Cables (3m) 2 Speaker Isolation Pads, dimensions each (D x W x H): 6.5 in. x 11 in. x 1.5 in. (170mm x 300mm x 40mm including angled addition) order in 4's	\$	99.00
MTC-SBT300	MTC-SBT300	300 Watt Multi-Tap 70V/100V Transformer for SB2210. Kit includes transformer (for mounting on existing studs inside input plate) with modular connectors for fast hook-up. Connect proper wire for tap setting. 300W, 150W, 75W at 70V/100V (plus 37W at 70V). Priced and packaged individually.	\$	100.00
CBT1K-ACC1	CBT1K-ACC1	Accessory Kit, Includes 2 sets MTC-CBT-FM3 Flush-Mount Wall Bracket and 1 pc MTC-CBT-OS3 Off-Set Bracket (for installing extender on the top). (Priced as the kit.)	\$	100.00
MTU-25	MTU-25	U-Bracket For Model AC25, Blk	\$	100.00
MTU-25-WH	MTU-25-WH	U-Bracket For Model AC25, White	\$	100.00
MTU-895	MTU-895	U Bracket for AC895, Blk	\$	102.00
MTU-895-WH	MTU-895-WH	U Bracket for AC895, White	\$	102.00
C62P	C62P	Ultra-Compact Mid-High Satellite Pendant Speaker. 2.5" driver, ideal for speech and mid-high music and for visually sensitive applications. Add up to 4 pics on a Control 50S/T (or 40 CS/T) subwoofer for full-range, 20W, 16 ohms, redundant suspension cable system included (priced as each; sold in pairs).	\$	105.00
C62P-WH	C62P-WH	Ultra-Compact Mid-High Satellite Pendant Speaker. 2.5" driver, ideal for speech and mid-high music and for visually sensitive applications. Add up to 4 pics on a Control 50S/T (or 40 CS/T) subwoofer for full-range, 20W, 16 ohms, redundant suspension cable system included (priced as each; sold in pairs), in white	\$	105.00

C1PRO	C1PRO	Compact Size Two-Way, 5.25" Low Frequency, .75" Polycarbonate Dome Tweeter, Molded Enclosure, Shielded Magnet, Black. Priced as Each. Packaged and sold in pairs.	\$	106.00
C1PRO-WH	C1PRO-WH	Compact Size Two-Way, 5.25" Low Frequency, .75" Polycarbonate Dome Tweeter, Molded Enclosure, Shielded Magnet, White. Priced as Each. Packaged and sold in pairs.	\$	106.00
MTU-16	MTU-16	U-Bracket For Model AC16, Blk	\$	108.00
MTU-16-WH	MTU-16-WH	U-Bracket For Model AC16, White	\$	108.00
CBT1K-ACC1-WH	CBT1K-ACC1-WH	CBT1K-ACC1 Accessory Kit in white.	\$	108.33
CSS-BB8X6	CSS-BB8X6	Pack of 6 pcs of 8" backcans for CSS8008 or CSS8018. Steel, zinc-plated, powder-coated, 4.8" (121 mm) deep, 5 knockouts (priced an sold as a pack of 6 pcs).	\$	109.00
MTC-24NC	MTC-24NC	Optional New Construction Bracket for Control 24C, 24CT, 24C Micro, 24CT Micro, and 24CT Micro Plus. Installs before Sheetrock as Cutout Template. Each Pack Contains 6 Pieces.	\$	113.00
MTC-42NC	MTC-42NC	New Construction Ring Brackets for Control 42C (each pack contains 6 pcs)	\$	114.00
IVX-806602	IVX-806602	Set of Hinges (yellow passivated) for Ivx DC/DS115/180/280.	\$	114.00
MTU-195	MTU-195	U Bracket for AC195, Blk	\$	114.00
MTU-195-WH	MTU-195-WH	U Bracket for AC195, White	\$	114.00
CONTROL 14C/T	CONTROL 14C/T	Two-Way 100 mm (4 in) Co-axial Ceiling Loudspeaker. 100 mm (4 in) high output driver with polypropylene cone and butyl rubber surround and 19 mm (3/4 in) soft-dome liquid-cooled tweeter, 74 Hz – 20 kHz bandwidth, wide 120° coverage, 87 dB sensitivity. Blind-mount backcan for quick and easy installation, dual conduit/cable clamp for in and thru cables. Combined 25 W multi-tap transformer at 70V/100V and 8Ω direct setting (30 W). White. Sold as each, packed in pairs. International master pack is 2 speakers.	\$	116.50
CONTROL 14C/T-BK	CONTROL 14C/T-BK	Two-Way 100 mm (4 in) Co-axial Ceiling Loudspeaker. 100 mm (4 in) high output driver with polypropylene cone and butyl rubber surround and 19 mm (3/4 in) soft-dome liquid-cooled tweeter, 74 Hz – 20 kHz bandwidth, wide 120° coverage, 87 dB sensitivity. Blind-mount backcan for quick and easy installation, dual conduit/cable clamp for in and thru cables. Combined 25 W multi-tap transformer at 70V/100V and 8Ω direct setting (30 W). Black. Sold as each, packed in pairs. International master pack is 2 speakers.	\$	116.50
MTU-26	MTU-26	U-Bracket For Model AC26, Blk	\$	120.00
MTU-26-WH	MTU-26-WH	U-Bracket For Model AC26, White	\$	120.00
IVX-802226	IVX-802226	Intellivox Wall Bracket 25mm, Set (3 pcs) Inc. fasteners, RAL9010. Made to Order Call for availability	\$	123.00
IVX-802236	IVX-802236	Intellivox Wall Bracket 35mm, Set (3 pcs) Inc. fasteners, RAL9010. Made to Order Call for availability	\$	123.00
CONTROL 26-DT	CONTROL 26-DT	200 mm (8 inch) Ceiling Speaker Transducer Assembly. Driver, Crossover Network and 70V/100V Transformer Assembly. Fits Standard Backcans for 8 Inch Speakers. Backcan must have 5+ inches depth. Coverage of 90°. Taps at 60W, 30W and 15W (Plus 7.5W at 70V Only). 1.9 kg (4.2 lb). Priced as Each, Packed as Pairs. See wb-site for list of compatible backcans and grilles.	\$	126.00
MTU-18	MTU-18	U-Bracket For Models AC18/xx, Blk	\$	126.00
MTU-18-WH	MTU-18-WH	U-Bracket For Models AC18/xx, White	\$	126.00
JBLPOLE-MA	JBLPOLE-MA	JBL speaker pole with manual adjustment from 36" to 55".	\$	126.09
MTC-26NC	MTC-26NC	Optional New Construction Bracket for Control 26C and Control 26CT, Installs Before Sheetrock as Cutout Template. Each Pack Contains 6 Pieces.	\$	129.00

		Lay-in Ceiling Tile Speaker, 8" driver, for US-size suspended grid ceilings (NOT for 600 x 600 mm metric grids), combined 70V/100V and low impedance direct operation, 20W at 8Ω, 10W multi-tap transformer with taps at 10W, 5W, 2.5W (and 1.3W for 70V only) via rotary tap-selector switch, max SPL of 108 (peaks of 114 dB) a 1m (low-Z), very low-profile at 103 mm (4.1") deep, bare-wire connection in protected compartment, very high 96 dB sensitivity, 100° conical coverage pattern, designed for high intelligibility, UL1480 and UL2043, white full-face grille. priced as each sold in pairs		
LCT 81C/T	LCT 81C/T		\$	130.00
		Compact 2-Way 100V/70V/8Ω Surface-Mount Loudspeaker. 5¼" LF and ¾" HF, 85 Hz – 18 kHz, 10 Watt Multi-Tap Transformer for 100V or 70V Distributed Speaker Lines (10W and 5W taps, plus 2.5W at 70V only), or 60W at 8Ω, ball-type wall-mount included. (priced as each; sold in pairs). 5¼" LF and ¾" HF, 85 Hz – 18 kHz, 10 Watt Multi-Tap Transformer for 100V or 70V Distributed Speaker Lines (10W and 5W taps, plus 2.5W at 70V only), or 60W at 8Ω, ball-type wall-mount included. (priced as each; sold in pairs)	\$	130.00
CSS-1S/T	CSS-1S/T		\$	130.00
CSS-H30	CSS-H30	30 Watt Paging Horn (Priced as each, 4 in masterpack)	\$	130.00
		Bolt on Transformer Module to allow CBT70J-1 or CBT70JE-1 Speaker to be used on 70V/100V Distributed Line Speaker. 120W Multi-Tap, Gland Nuts Provide Water Tight Cable Entrance and Exit. Sold and priced as each.	\$	130.00
MTC-CBT-70T	MTC-CBT-70T		\$	130.00
		Bolt on Transformer Module to allow CBT70J-1 or CBT70JE-1 Speaker to be used on 70V/100V Distributed Line Speaker. 120W Multi-Tap, Gland Nuts Provide Water Tight Cable Entrance and Exit. White. Sold and priced as each.	\$	131.00
MTC-CBT-70T-WH	MTC-CBT-70T-WH		\$	131.00
MTU-266-99	MTU-266-99	U bracket for AC266 and AC299, Blk	\$	132.00
MTU-266-99-WH	MTU-266-99-WH	U bracket for AC266 and AC299, White	\$	132.00
		Medium Output Ceiling Speaker Assembly. Complete Assembly Includes Backcan, Grille and Tile Rails. Very Wide 150° Coverage. Shallow 100 mm (4 in) Depth. 70V/100V Input Transformers with Taps at 25W and 12W (Plus 6W at 70V Only). Priced as Each, Packed as Pairs. Master Pack Quantity: 8 Pieces.	\$	132.30
C24CT MICROPLUS	C24CT MICROPLUS		\$	132.30
IVX-806618	IVX-806618	Intellivox Swivel Wall Bracket 45°, RAL9010. Made to Order Call for availability	\$	133.00
		4" Two-Way Vented Ceiling Speaker, 80Hz – 20kHz, 86dB Sensitivity, 80W Program and 40W Pink Noise Power Capacity, SonicGuard™ Overload Protection, 16 ohms, 130° Coverage, Packaged with Backcan, Grille, Support Plate and Tile Rails. Priced as Each, Packed as Pairs. Master Pack Quantity: 8 Pieces.	\$	134.40
CONTROL 24C	CONTROL 24C		\$	134.40
JBLTRIPOD-MA	JBLTRIPOD-MA	JBL speaker tripod with manual adjustment from 4' 2" to 6' 5".	\$	134.49
CONTROL 23-1L	CONTROL 23-1L	Low-Impedance-Only Version of Control 23-1 (&-WH), without 70V/100V transformer, 8 ohms only.	\$	135.00
CONTROL 23-1L-WH	CONTROL 23-1L-WH	Control 23-1L in white	\$	135.00
IVX-806608	IVX-806608	Intellivox Swivel Wall Bracket 90°, RAL9010. Made to Order Call for availability	\$	136.00
IVX-806668	IVX-806668	Intellivox Swivel Wall Bracket 90°, RAL9007. Made to Order Call for availability	\$	136.00
MTC-42MR	MTC-42MR	Mud-Ring Construction Brackets for C42C (each pack contains 6 pcs)	\$	138.08

IVX-802261	IVX-802261	Intellivox Wall Bracket 60mm, Set (3 pcs) Inc. fasteners, RAL9010. Made to Order Call for availability	\$	140.00
MTC-29MK	MTC-29MK	Marine Grille Kit for C29AV-1 Loudspeaker. Retrofit grille, adds extra durability when installing C29AV-1s in challenging corrosive environments such as sea-side restaurants, resorts in salt-air areas, water parks and swimming facilities. Kit includes extra-thick painted aluminum grille with WeatherMax™ backing plus stainless steel grille screws. Black.	\$	143.74
MTC-29MK-WH	MTC-29MK-WH	Marine Grille Kit for C29AV-1 Loudspeaker. Retrofit grille, adds extra durability when installing C29AV-1s in challenging corrosive environments such as sea-side restaurants, resorts in salt-air areas, water parks and swimming facilities. Kit includes extra-thick painted aluminum grille with WeatherMax™ backing plus stainless steel grille screws. Black.	\$	143.74
MTC-30MK	MTC-30MK	Marine Grille Kit for Control 30 Loudspeaker. Retrofit grille, adds extra durability when installing Control 30's in challenging corrosive environments such as cruise ships, sea-side restaurants, resorts in salt-air areas, water parks and swimming facilities. Kit includes extra-thick painted aluminum grille with WeatherMax™ backing plus stainless steel grille screws and protection caps for baffle screws. Black.	\$	143.85
MTU-566-99	MTU-566-99	U Bracket for AC566 and AC599, Blk	\$	144.00
MTU-566-99-WH	MTU-566-99-WH	U Bracket for AC566 and AC599, White	\$	144.00
Control 23-1	Control 23-1	3" Two-Way Vented Loudspeaker, Invisiball® Installation System (plus U-bracket attachment points). 70 Hz - 20 kHz Frequency Range. 50 Watts Cont. Pink Noise Power Handling (200W peak) at 8 ohms plus 70V/100V taps at 15W, 7.5W, 3.7W (& 1.8W at 70V only). Woven Fiberglass Woofer. Black. Priced as Each, Packed as Pairs. Master Pack Quantity: 6 Pieces.	\$	144.90
CONTROL 23-1-WH	CONTROL 23-1-WH	Control 23-1 in white.	\$	144.90
C24CT-BK	C24CT-BK	Control 24CT in Black. 4" two-way vented ceiling speaker, 80 Hz – 20 kHz, 86 dB sensitivity, 80W program and 40W pink noise power, for use on a 70.7V or 100V distributed line, switchable taps at 30W, 15W and 7.5W (plus 37W at 70.7V only, 130° coverage, packaged with backcan, grille, support plate and tile rails. (priced as each, sold in pairs).	\$	145.95
CONTROL 24CT	CONTROL 24CT	Control 24C with Transformer. For use on a 70.7V or 100V Distributed Line, Switchable Taps at 30W, 15W and 7.5W (Plus 3.7W at 70.7V only), No SonicGuard. Priced as Each, Packed as Pairs. Master Pack Quantity: 8 Pieces.	\$	145.95
MTC-24MR	MTC-24MR	Optional Mud (Plaster) Ring Construction Bracket for Control 24C, 24CT, 24C Micro, 24CT Micro, and 24CT Micro Plus. Installs before Sheetrock, Integral Ring Extension for Drywall Mudding. Each Pack Contains 6 Pieces.	\$	146.00
CONTROL 16C/T	CONTROL 16C/T	Two-Way 165 mm (6.5 in) Co-axial Ceiling Loudspeaker. 165 mm (6.5 in) high output driver with polypropylene cone and butyl rubber surround and 19 mm (3/4 in) soft-dome liquid-cooled tweeter, 62 Hz – 20 kHz bandwidth, 110° coverage, high 91 dB sensitivity. Blind-mount backcan for quick and easy installation, dual conduit/cable clamp for in and thru cables. Combined 30 W multi-tap transformer at 70V/100V and 8Ω direct setting (50 W). White. Sold as each, packed in pairs. International master pack is 2 speakers.	\$	149.50

CONTROL 16C/T-BK	CONTROL 16C/T-BK	Two-Way 165 mm (6.5 in) Co-axial Ceiling Loudspeaker. 165 mm (6.5 in) high output driver with polypropylene cone and butyl rubber surround and 19 mm (3/4 in) soft-dome liquid-cooled tweeter, 62 Hz – 20 kHz bandwidth, 110° coverage, high 91 dB sensitivity. Blind-mount backcan for quick and easy installation, dual conduit/cable clamp for in and thru cables. Combined 30 W multi-tap transformer at 70V/100V and 8Ω direct setting (50 W). Black. Sold as each, packed in pairs. International master pack is 2 speakers.	\$	149.50
MTC-24TR	MTC-24TR	Trim Ring for Retrofit Installations of Control 24 into Cutouts Up to 250mm (10") Diameter, White. Each Pack Contains 10 Pieces.	\$	152.25
MTC-26TR	MTC-26TR	Trim Ring for Retrofit Installations of Control 26 into Cutouts Up to 250mm (10") Diameter, White. Each Pack Contains 10 Pieces.	\$	152.25
NCST2120-X	NCST2120-X	2-Channel Transformer Kit for CSA2120	\$	153.71
351145-001	351145-001	RMC KIT, LSR6328P and LSR6312SP	\$	155.00
WMB-100	WMB-100	Wall mount bracket for AC895, AC195, AC266, AC299, AC566, and AC599, Blk	\$	156.00
WMB-100-WH	WMB-100-WH	Wall mount bracket for AC895, AC195, AC266, AC299, AC566, and AC599, White	\$	156.00
MTC-SB2W	MTC-SB2W	Bracket for Installing Control SB-2 to Wall or Corner.	\$	158.00
MTU-28	MTU-28	U-Bracket For Models AC28/xx, Blk	\$	158.00
MTU-28-WH	MTU-28-WH	U-Bracket For Models AC28/xx, White	\$	158.00
IVX-807402	IVX-807402	Set of Hinges (yellow passivated) for Ivx DC/DS430/500. Made to Order Call for availability	\$	161.00
MTC-30MK-WH	MTC-30MK-WH	Marine Grille Kit for Control 30 Loudspeaker. Retrofit grille, adds extra durability when installing Control 30's in challenging corrosive environments such as cruise ships, sea-side restaurants, resorts in salt-air areas, water parks and swimming facilities. Kit includes extra-thick painted aluminum grille with WeatherMax™ backing plus stainless steel grille screws and protection caps for baffle screws. White.	\$	162.00
CONTROL 25-1L	CONTROL 25-1L	Low-Impedance-Only Version of Control 25-1 (&-WH), without 70V/100V transformer, 8 ohms only.	\$	173.33
CONTROL 25-1L-WH	CONTROL 25-1L-WH	Control 25-1L in white	\$	173.33
MTC-26MR	MTC-26MR	Optional Mud (Plaster) Ring Construction Bracket for Control 26C and Control 26CT, Installs before Sheetrock, Integral Ring Extension for Drywall Mudding. Each Pack Contains 6 Pieces.	\$	174.00
CONTROL 26C	CONTROL 26C	6.5" Two-Way Vented Ceiling Speaker, 75Hz – 20kHz, 89dB Sensitivity, 150W Program and 75W Pink Noise Power Capacity, SonicGuard Overload Protection, 16 Ohms, 100° Coverage, Packaged With Backcan, Grille, Support Plate and Tile Rails. Priced as Each, Packed as Pairs. Master Pack Quantity: 4 Pieces.	\$	174.30
MTC-19NC	MTC-19NC	Optional New Construction Bracket for Control 19CS, Control 19CST, Control 226C/T, MTC-300BB8 and MTC-200BB6. Installs before Sheetrock as Cutout Template. Each Pack Contains 6 Pieces.	\$	175.00
C64P/T	C64P/T	Compact Full-Range Pendant Speaker. 4" (100 mm) driver with polypropylene cone, 120 degree conical coverage, 50 Watts Cont. Pink Noise Power Handling (200W peak) at 8 ohms, plus 30W 70V/100V multi-tap transformer, redundant suspension cable system included. Black. Priced as each, sold and packaged in pairs.	\$	180.00

C64P/T-WH	C64P/T-WH	Compact Full-Range Pendant Speaker. 4" (100 mm) driver with polypropylene cone, 120 degree conical coverage, 50 Watts Cont. Pink Noise Power Handling (200W peak) at 8 ohms, plus 30W 70V/100V multi-tap transformer, redundant suspension cable system included. White (-WH). Priced as each, sold and packaged in pairs.	\$	180.00
MTC-47NC	MTC-47NC	New construction Brackets for C47C/T & C47LP (each pack contains 6 pcs)	\$	181.00
305PMKII	305PMKII	S/M, 305PMKII	\$	186.25
Control 25-1	Control 25-1	5.25" Two-Way Vented Loudspeaker, Invisiball® Installation System (plus U-bracket attachment points). 60 Hz - 20 kHz Frequency Range. 100 Watts Cont. Pink Noise Power Handling (400W peak) at 8 ohms plus 70V/100V taps at 30W, 15W, 7.5W (& 3.7W at 70V only). Woven Fiberglass Woofer. Black or white (-WH). Priced as Each, Packed as Pairs.	\$	195.00
CONTROL 25-1-WH	CONTROL 25-1-WH	Control 25-1 in white.	\$	195.00
CONTROL 26CT	CONTROL 26CT	Control 26C with Transformer. For use on a 70.7V or 100V Distributed Line, Switchable Taps at 60W, 30W and 15W (Plus 7.5W at 70.7V only), No SonicGuard. Priced as Each, Packed as Pairs. Master Pack Quantity: 4 Pieces.	\$	196.35
CONTROL 126W	CONTROL 126W	Premium In-Wall Two-Way Loudspeaker with 6-1/2" (165 mm) Woofer. Polymer-Coated Aluminum-Cone Woofer With Pure Butyl Rubber Surround, Low-Diffraction Swivel Aimable Titanium Tweeter. High-Slope Crossover Network, Paintable, 98 mm (3-7/8 in) Depth (For Wallboard Plus Stud). 88 dB Sensitivity, 100 Watts (50W RMS/200W Peak), 38 Hz to 20 kHz Frequency Response. Sold in Pairs, Priced as Each.	\$	199.50
MTU-1	MTU-1	U-Bracket For Models AM7215/xx and AM5215/xx.	\$	200.00
C2PM	C2PM	One Control 2P Powered Master speaker, (without passive extension speaker) and power supply.	\$	200.00
JBLPOLE-GA	JBLPOLE-GA	JBL speaker pole featuring gass assist adjustment from 36" to 53".	\$	204.83
CONTROL 18C/T	CONTROL 18C/T	Two-Way 200 mm (8 in) Co-axial Ceiling Loudspeaker. 8 inch high output driver with polypropylene cone and butyl rubber surround and 25 mm (1 in) soft-dome liquid-cooled tweeter, 58 Hz – 20 kHz bandwidth, focused 90° coverage, high 92 dB sensitivity. Blind-mount backcan for quick and easy installation, dual conduit/cable clamp for in and thru cables. 60 W multi-tap transformer at 70V/100V and 8Ω direct setting for 90 Watts (260W peak). White. Sold as each, packed in pairs. Master pack = 2 speakers.	\$	205.00
CONTROL 18C/T-BK	CONTROL 18C/T-BK	Two-Way 200 mm (8 in) Co-axial Ceiling Loudspeaker. 8 inch high output driver with polypropylene cone and butyl rubber surround and 25 mm (1 in) soft-dome liquid-cooled tweeter, 58 Hz – 20 kHz bandwidth, focused 90° coverage, high 92 dB sensitivity. Blind-mount backcan for quick and easy installation, dual conduit/cable clamp for in and thru cables. 60 W multi-tap transformer at 70V/100V and 8Ω direct setting for 90 Watts (260W peak). Black (-BK). Sold as each, packed in pairs. Master pack = 2 speakers.	\$	205.00

		The M-PATCH 2 provides monitoring of up to two stereo input sources via two stereo outputs and offers excellent performance using passive circuitry. Front panel features include a large main volume attenuation control, an Aux level control and a STEREO/AUX input selector switch. Versatile monitoring controls include an A & B output destination selector; a Stereo/Mono summing switch and a Mute switch. A built-in headphone amp with a dedicated volume control and a 1/4-inch (6 mm) front panel headphone jack allows monitoring via headphones. Connection to a broad range of sources is facilitated by rear panel stereo XLR/TRS inputs, stereo unbalanced RCA inputs and two sets of balanced XLR outputs. Metal enclosure with included Rack-Mount Adaptors . Dimensions W x D x H: 8.7 in x 4.7 in. 3.4 in (220 mm x 120 mm x 86 mm) ; Weight: 2.2 lbs. (1.0 kg) Power requirements: Supplied 15 VDC power supply used to power headphone amplifier only.		
MPATCH2	MPATCH2		\$	206.71
		Professional Ceiling Speaker for Life-Safety Applications. UL1480 UUMW Listed for use in Fire Alarm and/or Emergency Communication Systems. 6.5" coax, 80 Hz – 20 kHz, all-in-one, backcan attached. (priced as each; sold in pairs)		
C26CT-LS	C26CT-LS		\$	212.10
		Compact Size Two-Way, 6.5" Low Frequency, 1" Pure Titanium Dome Tweeter, Molded Enclosure, Shielded Magnet, Black, Priced as Each. Master Pack Quantity: 2 Pieces.		
CONTROL 5	CONTROL 5		\$	218.00
		Control 126W With Transformer for Use on a 70.7V or 100V Distributed Line. Selectable Taps at 30W, 15W, and 7.5W (Plus 3.7W at 70V Only). (Priced as Each, Sold in Pairs).		
CONTROL 126WT	CONTROL 126WT		\$	220.50
104SET-BT-US	104SET-BT-US	JBL 104 Studio Monitors Bluetooth	\$	224.99
		Premium Monitor Speaker. 5.25" Two-Way Vented System, Highly Weather Resistant with Indoor/Outdoor, Stainless Steel Grille, 100° x 100° Coverage, 200 W Program Power, 70V/100V taps of 60W, 30W and 15W (and 7.5 W at 70V), plus 8 ohm Thru, Built-In Invisiball® Installation System. Includes MTC-PC Sealed-Entrance Panel Cover. Priced as Each, Packed as Pairs. Master Pack Quantity: 6 Pieces.		
CONTROL 25AV	CONTROL 25AV		\$	225.75
		Premium Monitor Speaker. 5.25" Two-Way Vented System, Highly Weather Resistant with Indoor/Outdoor, Stainless Steel Grille, 100° x 100° Coverage, 200 W Program Power, 70V/100V taps of 60W, 30W and 15W (and 7.5 W at 70V), plus 8 ohm Thru, Built-In Invisiball® Installation System, in white. Includes MTC-PC Sealed-Entrance Panel Cover. Priced as Each, Packed as Pairs. Master Pack Quantity: 6 Pieces.		
CONTROL 25AV-WH	CONTROL 25AV-WH		\$	225.75
		U-Bracket For Models AM7215/xx and AM5215/xx. White finish.		
MTU-1-WH	MTU-1-WH		\$	226.00
MTU-2	MTU-2	U-Bracket For Model AC2215/xx	\$	226.00
MTU-2-WH	MTU-2-WH	U-Bracket For Model AC2215/xx. White finish.	\$	226.00

ACTIVE-1	STUDIO ACCESSORIES	The ACTIVE-1 Provides seamless A/B switching of input sources and speaker systems and includes USB I/O for direct digital audio recording and playback when connected to a computer audio system. The ACTIVE-1 allows monitoring of four stereo input sources via four stereo outputs and delivers a full complement of audio monitoring functions, including: precision volume control, mono summing, mute, and dim. A footswitch-activated talk-back function, complete with on-board condenser microphone and selectable routing, makes the ACTIVE-1 the ideal solution for a broad range of studio production applications. Dimensions W x D x H: 13.0 in. x 7.5 in. x 5.0 in. (330 mm x 191 mm x 127 mm; Weight: 2.0 lb (0.9 kg) Power Requirements: Supplied 9 Volt DC Power Supply	\$	229.00
MTU-3	MTU-3	U-Bracket For Models AM7212/xx and AM5212/xx.	\$	234.00
MTU-3-WH	MTU-3-WH	U-Bracket For Models AM7212/xx and AM5212/xx. White finish.	\$	234.00
MTU-4	MTU-4	U-Bracket For Model AC2212/xx.	\$	234.00
MTU-4-WH	MTU-4-WH	U-Bracket For Model AC2212/xx. White finish.	\$	234.00
C65P/T	C65P/T	Compact Full-Range Pendant Speaker with RBI. 5-1/4" (130 mm) LF & silk dome HF, RBI Radiation Boundary Integrator® technology with 120 degree conical coverage, true coax, 75W at 8 ohms, plus 10W 70V/100V multi-tap transformer, redundant suspension cable system included (priced as each sold in pairs).	\$	235.00
C65P/T-WH	C65P/T-WH	Compact Full-Range Pendant Speaker with RBI. 5-1/4" (130 mm) LF & silk dome HF, RBI Radiation Boundary Integrator® technology with 120 degree conical coverage, true coax, 75W at 8 ohms, plus 10W 70V/100V multi-tap transformer, redundant suspension cable system included (priced as each sold in pairs), in white.	\$	235.00
CONTROL 47LP	CONTROL 47LP	Low-Profile version of C47D/T featuring RBI technology. Specs same as C47C/T except only 142 mm (5.6 in) deep, 68 Hz to 20 kHz. (priced as each; sold in pairs)	\$	239.40
CONTROL 45C/T	CONTROL 45C/T	Extremely consistent 120° broadband pattern control featuring JBL's exclusive conical Radiation Boundary Integrator® (RBI™) technology. Very consistent, full-range coverage of listening area while providing a small ceiling footprint. Wide, consistent coverage requires fewer speakers, reducing the cost of the installed system without sacrificing performance. Coaxial design featuring: 130 mm (5.25 in) polypropylene-coated paper cone with butyl rubber surround. 20 mm (.75 in) soft-dome tweeter on 210 mm (8.25 in) diameter wave guide. Bass extension down to 55 Hz. 8 ohm and 70V/100V operation. Integrated backcan for easy blind-mount" install. Packaged with grille and tile rails for easy installation.	\$	240.00
MTC-19MR	MTC-19MR	Optional Mud (Plaster) Ring Construction Bracket for Control 19CS, Control 19CST, and Control 226C/T. Installs before Sheetrock, Integral Ring Extension for Drywall Mudding. Each Pack Contains 6 Pieces.	\$	241.00
C25AV-LS	C25AV-LS	Premium 5.25" two-way, UL1480 UUMW rated for fire alarm use, highly weather resistant, aluminum grille, UL1480/UUMW rated, 110 x 85 coverage, 200W program power, 70V/100V taps at 60W, 30W, 15W (7.5W @ 70V only), See spec sheet for details of UL listing, MTC-PC included, black (priced as each, sold in pairs).	\$	243.60

C25AV-LS-WH	C25AV-LS-WH	Premium 5.25" two-way, UL1480 UUMW rated for fire alarm use, highly weather resistant, aluminum grille, UL1480/UUMW rated, 110 x 85 coverage, 200W program power, 70V/100V taps at 60W, 30W, 15W (7.5W @ 70V only), See spec sheet for details of UL listing, MTC-PC included, black (priced as each, sold in pairs)., in white	\$	243.60
CONTROL 128W	CONTROL 128W	Premium Quality In-Wall Two-Way Loudspeaker with 8" (200 mm) Woofer. Polymer-Coated Aluminum-Cone Woofer With Pure Butyl Rubber Surround, Low-Diffraction Swivel Aimable Titanium Tweeter. High-Slope Crossover Network, Paintable, 102 mm (4 in) Depth (For Wallboard Plus Stud). 90 dB Sensitivity, 60 Watts RMS (120W Program/240W Peak), 30 Hz to 20 kHz Frequency Response.	\$	245.70
IVX-802105	IVX-802105	Intellivox Cable entry cover box 2x M16, Inc. fasteners, RAL9010. Made to Order Call for availability	\$	248.00
306PMKII	306PMKII	S/M, 306PMKII	\$	248.75
PSB-1	PSB-1	2.0 active soundbar with an application-specific feature set for hotel guestrooms and cruise ship staterooms. Volume limiting switch places upper limit on SPL. Security lockout plate prevents guests from tampering with advanced settings. One RCA analog input. Four 19mm (0.75") HF drivers, and two 51mm (2.0") LF drivers. Class D amplifier delivers 20W per channel. 56Hz - 20KHz (+/- 3dB). Works with any TV's line level, analog, stereo output (fixed or variable volume). IR Learning allows the PSB-1 to be controlled by any remote. All table/wall mounting hardware included. Black. Sold and packed as each.	\$	249.00
PSB-1/230	PSB-1/230	Same as PSB-1, with 230 Volt power cord.	\$	249.00
CONTROL 85M	CONTROL 85M	Compact 5¼" Mushroom-Style Landscape Speaker. 5-1/4" (130 mm) polypropylene cone woofer with rubber surround & 3/4" (19 mm) tweeter, 55 Hz - 18 kHz, 80 Watts Cont. Pink Noise Power Handling (320W peak) at 8 ohms, plus 30W multi-tap transformer. IP-56 rated. Hunter green. Priced and packed individually.	\$	250.00
MTC-47MR	MTC-47MR	Mud-Ring construction Brackets for C47C/T & C47LP (each pack contains 6 pcs)	\$	251.00
C2PS	C2PS	Control 2P Stereo Set. Includes one C2PM powered master, one Passive Extension Speaker, one Power Supply and two Snap-On Angle Pedestals. Both speakers have a 5.25" Low Frequency and .75" Polycarbonate Dome Tweeter, Shielded Magnets, Molded Enclosures. Powered master incorporates 35 watts amplification x 2 channels; two Balanced XLR ¼" and two unbalanced RCA inputs; Stereo Volume Control; Stereo Headphone Jack; HF Contour Control.	\$	260.00
CONTROLCRV	CONTROLCRV	Curved-Design Dual 4" Speaker, selectable 70V/100V or 4 ohm, indoor/outdoor, combinable, 80 Hz - 20 kHz, 75W cont pink (300W peak), wall-mount bracket included (prices as each and sold individually), black. Master Pack Quantity: 4 Pieces	\$	261.45
CONTROLCRV-WH	CONTROLCRV-WH	Curved-Design Dual 4" Speaker, selectable 70V/100V or 4 ohm, indoor/outdoor, combinable, 80 Hz - 20 kHz, 75W cont pink (300W peak), wall-mount bracket included (prices as each and sold individually), white. Master Pack Quantity: 4 Pieces	\$	261.45
CONTROL 19CS	CONTROL 19CS	8" In-Ceiling Subwoofer, Nested Chamber™ Design, Linear Aperture™ Port, 42Hz – 200Hz, 200W Program and 100W Pink Noise Power Capacity, SonicGuard Overload Protection, 8 ohms, Packaged with Backcan, Support Plate and Tile Rails. Priced as Each, Packed as Pairs. Master Pack Quantity: 2 Pieces.	\$	263.55

MTC-48TRx12	MTC-48TRx12	Tile rails for using many of JBL's ceiling speaker in 1200 mm (48 in) ceiling tile grid systems. Inverted-V design. Can be used with 8124/28, Control 19CS models. Control 24C Micro models, Control 24C models, Control 26 models, Control 40 Series models, and Control 226C/T. (Sold and packed as a kit of 12 tile rails (for 6 spkrs).	\$	269.00
MTC-300BB12	MTC-300BB12	Best-in-Class Three Cubic Foot Back Box for 12" Models. Rectangular with Extra-Thick 16 Gauge Metal and Heavy Duty ½" MDF Reinforcement on Top and Side Panels. Fits Control 321C, 321CT, 322C, 322CT & 321CS. 23.1" x 18.2" (20" Incl. Side Tabs) x 12.8" Deep. NOW UL LISTED	\$	269.00
CONTROL 128WT	CONTROL 128WT	Control 128W With Transformer for Use on a 70.7V or 100V Distributed Line. Selectable Taps at 50W, 25W, and 12W (Plus 6W at 70V Only). (Priced as Each, Sold in Pairs).	\$	270.90
CONTROL 47C/T	CONTROL 47C/T	Wide-coverage, extended bass ceiling spkr feature RBI. 6.5" two-way, 120 deg consistent coverage, 55 Hz - 20 kHz, 91 dB sens, taps at 60W, 30W, 15W (and 7.5W @ 70V) plus 8 ohm direct. (priced as each, sold in pairs.)	\$	278.25
CONTROL 19CST	CONTROL 19CST	Control 19CS with Subwoofer Based Transformer. For use on a 70.7V or 100V Distributed Line, Switchable Taps at 60W, 30W and 15W (Plus 7.5W at 70.7V only), No SonicGuard. Priced as Each, Packed as Pairs. Master Pack Quantity: 2 Pieces.	\$	285.60
CONTROL 227C	CONTROL 227C	6.5" Coax Ceiling Loudspeaker with Compression Driver. Broadband 120° Coverage. 150 Watts, 43 Hz to 19kHz Frequency Response, 90 dB Sensitivity. 1" Exit Compression Driver. 8 ohms. 12" Round Ported Baffle x 5.8" Deep. (Priced and Sold as Each). UL LISTED	\$	292.95
CONTROL 28-1L	CONTROL 28-1L	Low-Impedance-Only Version of Control 28-1 (&-WH), without 70V/100V transformer, 8 ohms only.	\$	295.00
CONTROL 28-1L-WH	CONTROL 28-1L-WH	Control 28-1L in white	\$	295.00
VLA-C125S-ACC	VLA-C125S-ACC	Kit for wiring of 3 VLA-C-125S subwoofers in cardioid configuration (2 front-facing and 1 rear-facing). Allows for neat, unexposed inter-cabinet wiring via the tops and bottoms of cabinets.	\$	300.00
NCSA140Z-U-US	NCSA140Z-U-US	1 x 40W DriveCore Amplifier, Fanless, 4ohm/8ohm/70V/100V, 1U Half-Rack, Mounting kit	\$	309.12
308PMKII	308PMKII	S/M, 308PMKII	\$	311.25
JRX212	JRX212	12" two-way stage monitor or front of house passive speaker system; 1000 Watt peak power handling, 129dB Maximum SPL, 8 ohms. 19mm MDF enclosure, 18-gauge hexagon perforated steel grille. Net Weight 19.5kg (43 lbs).	\$	312.00
CONTROL 28-1	CONTROL 28-1	8" Two-Way Vented Loudspeaker, Invisiball® Installation System (plus U-bracket attachment points). 45 Hz - 20 kHz Frequency Range. 120 Watts Cont. Pink Noise Power Handling (480W peak) at 8 ohms plus 70V/100V taps at 60W, 30W, 15W (& 7.5W at 70V only). Woven Fiberglass Woofer. Black or white (-WH). Priced as Each, Packed as Pairs.airs.	\$	315.00
CONTROL 28-1-WH	CONTROL 28-1-WH	Control 28-1 in white.	\$	315.00
JBLTRIPOD-GA	JBLTRIPOD-GA	JBL speaker tripod featuring gass assist adjustment from 3' 8" to 6' 7"	\$	318.17
CONTROL HST	CONTROL HST	Control HST - Wide-Coverage On-Wall Speaker	\$	332.00
CONTROL HST-WH	CONTROL HST-WH	Control HST - Wide-Coverage On-Wall Speaker	\$	332.00
CONTROL 227CT	CONTROL 227CT	Control 227C with Pre-Attached 60 Watt 70V/100V Multi-Tap Transformer. Taps at 68 W, 34W and 17W (plus 8.5W at 70V only). 12" Round Baffle x 5.8" Deep. (Priced and Sold as Each). UL LISTED	\$	333.90
CONTROL 47HC	CONTROL 47HC	PREMIUM HIGH-CEILING COAX w/ 6.5"	\$	336.00

C67P/T	C67P/T	Extended-Bass Full-Range Pendant Speaker with RBI. 6-1/2" (165 mm) LF & silk dome HF, RBI Radiation Boundary Integrator® technology with 120 degree conical coverage, true coax, 75W at 8 ohms plus 60W 70V/100V multi-tap transformer, redundant suspension cable system included (priced as each; sold in pairs).	\$	340.00
C67P/T-WH	C67P/T-WH	Extended-Bass Full-Range Pendant Speaker with RBI. 6-1/2" (165 mm) LF & silk dome HF, RBI Radiation Boundary Integrator® technology with 120 degree conical coverage, true coax, 75W at 8 ohms plus 60W 70V/100V multi-tap transformer, redundant suspension cable system included (priced as each; sold in pairs), in white.	\$	340.00
CONTROL 328C	CONTROL 328C	8" Coax Ceiling Speaker with 12" Waveguide. Broadband 120° Coverage. 250 Watts, 45 Hz to 18 kHz Frequency Response, 93 dB Sensitivity. 2412H Compression driver. 12" Round Ported Baffle/Waveguide x 6.3" Deep. UL LISTED	\$	365.40
CONTROL 226C/T	CONTROL 226C/T	6.5" Coax Ceiling Loudspeaker. True-Broadband 120° Coverage. 150 Watts, 47 Hz to 19kHz Frequency Response, 90 dB Sensitivity. 1" Exit Compression Driver. 8 ohms Plus 70V/100V Taps at 60W, 30W, 15W (And 7.5W @ 70V). 13" Round Ported Baffle x 9.7" Deep. (Priced as Each, Sold in Pairs).	\$	367.50
JRX215	JRX215	15" two-way front of house passive speaker system; 1000 Watt peak power handling, 128dB Maximum SPL, 8 ohms. 19mm MDF enclosure, 18-gauge hexagon perforated steel grille. Net Weight 27.4kg (60.5 lbs).	\$	374.00
CONTROL 88M	CONTROL 88M	High-Power 8" Mushroom-Style Landscape Speaker. 8" (200 mm) polypropylene cone woofer with rubber surround & 1" (25 mm) tweeter, 47 Hz - 16 kHz, 120 Watts Cont. Pink Noise Power Handling (480W peak) at 8 ohms, plus 60W multi-tap transformer. IP-56 rated. Hunter green. Priced and packed individually.	\$	375.00
AWC62	AWC62	6.5" 2-Way All-Weather Compact Co-axial Loudspeaker. 110° x 110° broadband control, co-ax driver with 165 mm (6.5 in) Kevlar-reinforced woofer with 38 mm 1.5 in) voice coil and 25 mm (1 in) compression driver. Excellent clarity extended frequency response. 175 Watt power handling (700 W peaks), 70 Hz - 18 kHz frequency range, overload HF protection, 120 Watt 70V/100V multi-tap or direct 8 ohm low-impedance. U-Bracket included. Light Gray, paintable. Sold and packed as each.	\$	380.00
AWC62-BK	AWC62-BK	Same as AWC62, in black. Sold and packed as each.	\$	380.00
AC15	AC15	Ultra-Compact 2-Way Loudspeaker with 1 x 5.25" LF. 90° x 90° Coverage, Passive. Suspension Eyebolts Not Included. Optional U-Bracket Model MTU-15. Sold as 2 per carton.	\$	383.00
CONTROL 40CS/T	CONTROL 40CS/T	Direct-Radiating In-Ceiling Subwoofer with 8" driver, built-in crossover network with outputs for 2 or 4 pcs of Control 42C satellite speakers, 30 Hz - 300 Hz, 200W program, 100W pink noise, 70V/100V taps at 80W, 40W, 20W (and 10W @ 70V), plus 8 ohm direct, (priced as each, sold in pairs)	\$	388.50
CONTROL SB-2	CONTROL SB-2	Slot-Loaded Vented Bandpass Subwoofer, Stereo, with Dual Voice-Coil 10" Transducer, Trapezoidal Enclosure for easy Corner Placement, 38Hz – 160Hz, 340W Program, 100dB Sensitivity, 8 ohm Stereo Inputs with High-Pass Satellite Outputs.	\$	390.60
CONTROL 50S/T	CONTROL 50S/T	Compact surfact-mount subwoofer with built-in crossover. 200 mm (8 in) long-throw woofer, 100W cont pink noise (400W peak), selectable 70V/100V or low-impedance, drives 2 or 4 satellite speakers (C42C, C52 or C62P), wall-mount bracket included, black (priced as each;.	\$	393.75

CONTROL 50S/T-WH	CONTROL 50S/T-WH	Compact surfact-mount subwoofer with built-in crossover. 200 mm (8 in) long-throw woofer, 100W cont pink noise (400W peak), selectable 70V/100V or low-impedance, drives 2 or 4 satellite speakers (C42C, C52 or C62P), wall-mount bracket included, black (priced as each;.	\$	393.75
C67HC/T	C67HC/T	Narrow-coverage High-Ceiling Pendant Speaker with RBI. 6-1/2" (165 mm) LF & silk dome HF, RBI Radiation Boundary Integrator® technology with narrow 75 degree conical coverage, true coax, excellent clarity in high-ceiling installs and reverberant spaces, 75W at 8 ohms plus 60W 70V/100V multi-tap transformer, redundant suspension cable system included (priced as each; sold in pairs).	\$	400.00
C67HC/T-WH	C67HC/T-WH	Narrow-coverage High-Ceiling Pendant Speaker with RBI. 6-1/2" (165 mm) LF & silk dome HF, RBI Radiation Boundary Integrator® technology with narrow 75 degree conical coverage, true coax, excellent clarity in high-ceiling installs and reverberant spaces, 75W at 8 ohms plus 60W 70V/100V multi-tap transformer, redundant suspension cable system included (priced as each; sold in pairs), in white.	\$	400.00
CONTROL 328CT	CONTROL 328CT	Control 328C with pre-attached 60 Watt 70V/100V Multi-Tap Transformer. Taps at 68W, 34W & 17W (Plus 8.5W at 70V Only). 12" Round Ported Baffle with Waveguide, Depth 8.6". UL LISTED	\$	410.55
C60PS/T	C60PS/T	High impact, 150 Watt direct radiating pendant subwoofer with built-in passive crossover for up to four satellite speakers. 200 mm (8 in) long-excursion driver. 8 ohm (150 Watt) and 70V/100V (100 Watt) operation. Hanging hardware with 4.5 m (15 foot) galvanized steel cable and easy to adjust clamp. Stylish design, available in black or white (-WH). UL listed (speaker and hanging cable system).(priced as each; sold in pairs).	\$	415.00
C60PS/T-WH	C60PS/T-WH	High impact, 150 Watt direct radiating pendant subwoofer with built-in passive crossover for up to four satellite speakers. 200 mm (8 in) long-excursion driver. 8 ohm (150 Watt) and 70V/100V (100 Watt) operation. Hanging hardware with 4.5 m (15 foot) galvanized steel cable and easy to adjust clamp. Stylish design, available in black or white (-WH). UL listed (speaker and hanging cable system).(priced as each; sold in pairs).	\$	415.00
NVMA160-0-US	NVMA160-0-US	VMA 160: (5) input channel x (1) 60W output channel Mixer/Amplifier	\$	434.00
CONTROL 321C	CONTROL 321C	Premium 12" Coax Ceiling Loudspeaker. True-Broadband 90° Coverage. 250 Watts, 34 Hz to 18 kHz Frequency Response, 94 dB Sensitivity. 2412H Compression Driver. 14.4" Square Ported Baffle x 8.8" Deep. EZ-Rail™ For Ease of Installation. UL LISTED.	\$	450.45
AC15-WH	AC15-WH	AC15 in white.	\$	460.00
EON610	EON610	10" two-way stage monitor or front of house powered speaker system; 1000 Watt peak power rating, 124dB Maximum SPL, Image Control Waveguide, Bluetooth v4.0 control, Two channel mixer with XLR-1/4" combo inputs, 3 x M10 suspension points, plastic enclosure. Weight 11.79kg (26 lbs).	\$	485.00

		High Output Indoor/Outdoor Monitor Speaker. 150W Pink Noise, 300W Program Power, 92 dB Sensitivity. 70V/100V Taps at 110W, 55W, & 28W (and 14W at 70V) plus 8 ohm Thru. 110° x 80° Coverage with Rotatable Horn. Built-In Invisiball® Installation System plus Ten M6 Suspension Points. Kevlar Cone Woofer and Titanium Compression Driver. Includes Sonicguard(tm) Overload Protection. Includes MTC-PC2 Sealed-Entrance Panel Cover. (Priced and Packed as Each)		
C29AV-1	C29AV-1		\$	490.35
		High Output Indoor/Outdoor Monitor Speaker. 150W Pink Noise, 300W Program Power, 92 dB Sensitivity. 70V/100V Taps at 110W, 55W, & 28W (and 14W at 70V) plus 8 ohm Thru. 110° x 80° Coverage with Rotatable Horn. Built-In Invisiball® Installation System plus Ten M6 Suspension Points. Kevlar Cone Woofer and Titanium Compression Driver. Includes Sonicguard(tm) Overload Protection. Includes MTC-PC2 Sealed-Entrance Panel Cover, in White. (Priced and Packed as Each).		
C29AV-WH-1	C29AV-WH-1		\$	490.35
		Control 321C with pre-attached 60 Watt 70V/100V Multi-Tap Transformer. Taps at 68W, 34W and 17W (Plus 8.5W at 70V Only). 14.4" Square Ported Baffle x 9.5 Deep. EZ-Rail for Ease of Installation. UL LISTED		
CONTROL 321CT	CONTROL 321CT		\$	495.60
		4 Input - 1 Output Mixer, Fanless, 1U Half-Rack, Mounting kit included		
NCSM14-U-US	NCSM14-U-US		\$	498.48
LSR310S	LSR310S	10-inch powered subwoofer.	\$	499.00
		50 cm Straight Line Array Column with 8 x 2" Drivers and Constant Beamwidth Technology, 20° vertical coverage, music (flat)/speech switch, 60W multi-tap transformer or 8 ohms, 80 Hz – 20 kHz, 150W cont pink (600W peak), wall bracket included. (priced and sold individually)		
CBT 50LA-1	CBT 50LA-1		\$	505.00
		50 cm Straight Line Array Column with 8 x 2" Drivers and Constant Beamwidth Technology, 20° vertical coverage, music (flat)/speech switch, 60W multi-tap transformer or 8 ohms, 80 Hz – 20 kHz, 150W cont pink (600W peak), wall bracket included. (priced and sold individually)		
CBT 50LA-1-WH	CBT 50LA-1-WH		\$	505.00
		8" 2-Way All-Weather Compact Co-axial Loudspeaker. 120° x 120° broadband control, co-ax driver with 200 mm (8 in) Kevlar-reinforced woofer and 25 mm (1 in) compression driver with high-temp polymer diaphragm. Excellent clarity with extended frequency response. 250 Watt power handling (1000 Watt peaks), 80 Hz - 20 kHz frequency range, overload HF protection, 200 Watt 70V/100V multi-tap or direct 8? low-impedance. U-Bracket included. Gray or black (-BK), paintable. Sold and packed as each.		
AWC82	AWC82		\$	505.00
		8" 2-Way All-Weather Compact Co-axial Loudspeaker. 120° x 120° broadband control, co-ax driver with 200 mm (8 in) Kevlar-reinforced woofer and 25 mm (1 in) compression driver with high-temp polymer diaphragm. Excellent clarity with extended frequency response. 250 Watt power handling (1000 Watt peaks), 80 Hz - 20 kHz frequency range, overload HF protection, 200 Watt 70V/100V multi-tap or direct 8? low-impedance. U-Bracket included. Gray or black (-BK), paintable. Sold and packed as each.		
AWC82-BK	AWC82-BK		\$	505.00
		1 x 80W DriveCore Amplifier, Fanless, 4ohm/8ohm/70V/100V, 1U Half-Rack, Mounting kit		
NCSA180Z-U-US	NCSA180Z-U-US		\$	539.00
		2 x 40W DriveCore Amplifier, Fanless, 4ohm/8ohm/70V/100V, 1U Half-Rack, Mounting kit		
NCSA240Z-U-US	NCSA240Z-U-US		\$	540.60
		50CM Tall Column Spkr, EN54 1 per carton, 1 per Masterpack		
CBT 50LA-LS	CBT 50LA-LS		\$	545.00
		50CM Tall Column Spkr, WH,EN54 1 per carton, 1 per Masterpack		
CBT 50LA-LS-WH	CBT 50LA-LS-WH		\$	545.00

EON612	EON612	12" two-way stage monitor or front of house powered speaker system; 1000 Watt peak power rating, 126dB Maximum SPL, Image Control Waveguide, JBL Low-Frequency Waveguide, Bluetooth v4.0 control, Two channel mixer with XLR-1/4" combo inputs, 3 x M10 suspension points, plastic enclosure. Weight 14.96kg (33 lbs).	\$	546.00
NVMA1120-0-US	NVMA1120-0-US	VMA 1120: (5) input channel x (1) 120W output channel Mixer/Amplifier	\$	554.00
CONTROL 312CS	CONTROL 312CS	12" In-Ceiling Subwoofer. 400 Watts, 30 Hz – 4.5 kHz Frequency Response, 93 dB Sensitivity. 14.4" Square Ported Baffle x 6.3" Deep. EZ-Rail for Ease of Installation. UL LISTED	\$	558.60
IVX-20021	IVX-20021	Intellivox 115 series Custom Color Surcharge . Made to Order Call for availability	\$	560.00
JRX225	JRX225	Dual 15" two-way front of house passive speaker system; 2000 Watt peak power handling, 133dB Maximum SPL, 4 ohms. 19mm MDF enclosure, 18-gauge hexagon perforated steel grille. Net Weight 42.6kg (94 lbs).	\$	562.00
NCSA2120Z-U-US	NCSA2120Z-U-US	2 x 120W DriveCore Amplifier, Fanless, 4ohm/8ohm/70V/100V, 1U Half-Rack, Mounting kit	\$	593.58
IVX-20022	IVX-20022	Intellivox 180 series Custom Color Surcharge . Made to Order Call for availability	\$	599.00
EON615	EON615	Powered 15" two-way system featuring JBL's new waveguide technology and Bluetooth control.	\$	607.00
JRX218S	JRX218S	18" passive compact subwoofer; 1400 Watt peak power handling, 127dB Maximum SPL, 4 ohms. 19mm MDF enclosure, 18-gauge hexagon perforated steel grille. Net Weight 40.4kg (89 lbs).	\$	624.00
PRX412M	PRX412M	12" two-way stage monitor or front of house passive speaker system; 1200 Watt peak power handling , 126dB Maximum SPL , 8 ohms. DuraFlex™-covered 18mm plywood enclosure, 16 gauge cloth-backed steel grille, dual 36 mm pole sockets, non-skid rubber feet. 12 M10 suspension points. Net Weight 17.5kg (38 lbs.)	\$	624.00
DUR386612	DUR386612	PROGRAM SET UNIVERSAL USB.	\$	628.00
VRX-SMAF	VRX-SMAF	Small Array Frame for suspending VRX928LA and VRX915S arrays. Includes 2 x quick release pins, 2 x shackles, 2 x drop levers..	\$	629.00
NCSA1120Z-U-US	NCSA1120Z-U-US	1 x 120W DriveCore Amplifier, Fanless, 4ohm/8ohm/70V/100V, 1U Half-Rack, Mounting kit	\$	629.88
C50PACK	C50PACK	Subwoofer-Satellite System with 4 Satellite Speakers. Includes 1 pc Control 50S/T and 4 pcs Control 52, 30 – 20 kHz response, 100W, selectable 70V/100V or 4 ohms, wall-mount brackets included, black. (each pack contains 1 subwoofer + 4 satellites)	\$	640.50
C50PACK-WH	C50PACK-WH	Subwoofer-Satellite System with 4 Satellite Speakers. Includes 1 pc Control 50S/T and 4 pcs Control 52, 30 – 20 kHz response, 100W, selectable 70V/100V or 4 ohms, wall-mount brackets included, black or white. (each pack contains 1 subwoofer + 4 satellites), in white	\$	640.50
CONTROL 322C	CONTROL 322C	High-Power 12" Coax Ceiling Loudspeaker with Medium Format Compression Driver. True Broadband 90° Coverage. 400 Watts, 32 Hz to 20 kHz Frequency Response, 95 dB Sensitivity. 2407H Compression Driver. 14.4" Square Ported Baffle x 8.8" Deep. EZ-Rail for Ease of Installation. UL LISTED	\$	655.20
IVX-20023	IVX-20023	Intellivox 280 series Custom Color Surcharge . Made to Order Call for availability	\$	660.00
NVMA1240-0-US	NVMA1240-0-US	VMA 1240: (5) input channel x (1) 240W output channel Mixer/Amplifier	\$	674.00

NVMA260-0-US	NVMA260-0-US	VMA 260: (5) input channel x (2) 60W output channel Mixer/Amplifier	\$	678.42
PRX415M	PRX415M	15" two-way stage monitor or front-of-house passive speaker system; 1200 Watt peak power handling, 129dB Maximum SPL, 8 ohms. DuraFlex™-covered 18mm plywood enclosure, 16 gauge cloth-backed steel grille, dual 36 mm pole sockets, non-skid rubber feet. 12 M10 suspension points. Net Weight 21kg (46 lbs.)	\$	686.00
EON One Compact-NA	EON One Compact		\$	686.25
NCSA280Z-U-US	NCSA280Z-U-US	2 x 80W DriveCore Amplifier, Fanless, 4ohm/8ohm/70V/100V, 1U Half-Rack, Mounting kit	\$	686.46
LSR705i	LSR705i	Compact high output two-way externally powered studio monitor with 725G five-inch (127 mm) high-excursion low frequency transducer and 2409H high-frequency compression driver; Patent-pending Image Control Waveguide provides a seamless crossover transition and detailed imaging. 39Hz - 36 kHz frequency range; 107dB Maximum Peak SPL; Dividing Network Transition Frequency: 1.9 kHz. Dividing Network can be bypassed for bi-amplified operation. Birch Plywood enclosure includes rear and bottom mounting points; Not intended for stand-alone use. Complete system requires HARMAN Professional signal processor and external Crown Power Amplifier (not Included.)	\$	690.00
NCSMA180-U-US	NCSMA180-U-US	4 input - 1 x 80W DriveCore Mixer-Amp, Fanless, 4ohm/8ohm/70V/100V, 1U Half-Rack, Mounting kit	\$	695.96
NCSM28-U-US	NCSM28-U-US	8 Input - 2 Output Mixer, Fanless, 1U Full-Rack, Mounting kit included	\$	710.00
CONTROL 322CT	CONTROL 322CT	Control 322C with pre-attached 100 Watt 70V/100V Multi-Tap Transformer. Taps at 100W, 50W & 25W (Plus 12.5W at 70V Only). 14.4" Square Ported Baffle x 9.5" Deep. EZ-Rail for Ease of Installation. UL LISTED	\$	711.90
CONTROL SB-210	CONTROL SB-210	Control sb-210	\$	713.00
IVX-20030	IVX-20030	Intellivox-HP-DS170 Surcharge Custom Color. Made to Order Call for availability	\$	719.00
AC895	AC895	8" 2-way full-range system, rotatable 90° x 50° waveguide coverage pattern with 2414H-C 25mm (1 in) exit, 25mm (1 in) voice coil.	\$	720.00
AC895-WH	AC895-WH	AC895 in White	\$	720.00
IVX-20033	IVX-20033	Intellivox 380 series Custom Color Surcharge. Made to Order Call for availability	\$	721.00
PRX412M-WH	PRX412M-WH	12" two-way stage monitor or front of house passive speaker system; 1200 Watt peak power handling, 126dB Maximum SPL, 8 ohms. White DuraFlex™-covered 18mm plywood enclosure, 16 gauge cloth-backed steel grille. 12 M10 suspension points. Net Weight 17.5kg (38 lbs.)	\$	730.00
NVMA2120-0-US	NVMA2120-0-US	VMA 2120: (8) input channel x (2) 120W output channel Mixer/Amplifier	\$	734.00
CBT 70JE-1	CBT 70JE-1	70 cm Extension for CBT 70J-1 Line Array, 4 x 5" Drivers. 500W continuous pink noise, 8 ohms, linking bracket included, 70 cm tall for 140 cm tall CBT 70J-1/JE-1 array, connect 70J-1 and 70JE-1 in parallel. (priced and sold individually). Combined with CBT 70J-1, system response is 45 Hz – 20 kHz with well controlled pattern to 250 Hz.	\$	735.00
CBT 70JE-1-WH	CBT 70JE-1-WH	70 cm Extension for CBT 70J-1 Line Array, 4 x 5" Drivers. 500W continuous pink noise, 8 ohms, linking bracket included, 70 cm tall for 140 cm tall CBT 70J-1/JE-1 array, connect 70J-1 and 70JE-1 in parallel. (priced and sold individually). Combined with CBT 70J-1, system response is 45 Hz – 20 kHz with well controlled pattern to 250 Hz.	\$	735.00
JBLCSM21V	JBLCSM21V	2 x 1 Stereo/Mono Public Address Mixer	\$	739.96

NCSA1300Z-0-US	NCSA1300Z-0-US	Two-Way, High Output Indoor-Outdoor Monitor Loudspeaker with 260mm (10 in) LF and 2414H-C Compression Driver. Extended Bandwidth, Extremely Smooth Response. Outdoor Capability to IP-55. 33 Hz – 19 kHz. 250 Watts, 92 dB Sensitivity. Included InvisiBall® Hardware Plus Ten 6 mm Attachment Points For Suspension and Optional U-Bracket. Includes 70V/100V Input Line Transformer with Taps at 150W, 75W, and 38W (Plus 19W At 70V only), Plus 8 ohm Bypass Position. 593 x 372 x 345 mm (23.3 x 14.6 x 13.5 in). 18.8 kg (41.5 lb). Priced as Each, Packed as Singles.	\$	749.00
CONTROL 31	CONTROL 31	Two-Way, High Output Indoor-Outdoor Monitor Loudspeaker with 260mm (10 in) LF and 2414H-C Compression Driver. Extended Bandwidth, Extremely Smooth Response. Outdoor Capability to IP-55. 33 Hz – 19 kHz. 250 Watts, 92 dB Sensitivity. Included InvisiBall® Hardware Plus Ten 6 mm Attachment Points For Suspension and Optional U-Bracket. Includes 70V/100V Input Line Transformer with Taps at 150W, 75W, and 38W (Plus 19W At 70V only), Plus 8 ohm Bypass Position. 593 x 372 x 345 mm (23.3 x 14.6 x 13.5 in). 18.8 kg (41.5 lb). Priced as Each, Packed as Singles.	\$	750.00
CONTROL 31-WH	CONTROL 31-WH	10" 2-way full-range system, rotatable 90° x 50° waveguide coverage pattern with 2408H-2 25mm (1 in) exit, 38mm (1.5 in) voice coil.	\$	750.00
AC195	AC195	AC195 in White	\$	750.00
AC195-WH	AC195-WH	Intellivox 430 series Custom Color Surcharge . Made to Order Call for availability	\$	753.00
IVX-20043	IVX-20043	Compact, Low Profile, High-Power Subwoofer with 2 x 250mm (10 Inch) Woven-Fiberglass Cone Drivers. 500 Watts Cont. Pink Noise Power Handling (2000W peak), 13 M6 Suspension Points, feet, Optional U-bracket. 38 Hz-500 Hz Frequency Range, 355 x 590 x 570 mm, (14 x 23.3 x 22.5 In). Black. Priced and sold individually.	\$	775.00
CONTROL SB2210	CONTROL SB2210	Control SB2210 in white (-WH)	\$	775.00
CONTROL SB2210-WH	CONTROL SB2210-WH	Intellivox 500 series Custom Color Surcharge . Made to Order Call for availability	\$	794.00
IVX-20063	IVX-20063	15" two-way stage monitor or front- of- house passive speaker system; 1200 Watt peak power handling , 129dB Maximum SPL , 8 ohms. White DuraFlex™-covered 18mm plywood enclosure, 16 gauge cloth-backed steel grille. 12 M10 suspension points. Net Weight 21kg (46 lbs.)	\$	810.00
PRX415M-WH	PRX415M-WH	8 input - 2 x 40W DriveCore Mixer-Amp, Fanless,	\$	812.14
NCSMA240-U-US	NCSMA240-U-US	4ohm/8ohm/70V/100V, 1U Full-Rack, Mounting kit	\$	850.00
AC115S-WH	AC115S-WH	AC115S in White	\$	856.00
IVX-20010	IVX-20010	Weather-proofing kit, Intellivox 115/180 series. Only for amp at top units.. Made to Order Call for availability	\$	856.00
IVX-20012	IVX-20012	Weather-proofing kit, Intellivox 280/380 series. Only for amp at top units.. Made to Order Call for availability	\$	856.00
IVX-20014	IVX-20014	Weather-proofing kit, Intellivox 430 series. Only for amp at top units.. Made to Order Call for availability	\$	856.00
IVX-20016	IVX-20016	Weather-proofing kit, AXYS Intellivox 500 series. Only for amp at top units.. Made to Order Call for availability	\$	856.00
AC25	AC25	Ultra-Compact 2-Way Loudspeaker with 2 x 5.25" LF. 90° x 90° Coverage, Passive. Suspension Eyebolts Not Included. Optional U-Bracket Model MTU-25.	\$	856.00
AC25-WH	AC25-WH	AC25 in white.	\$	856.00

		High Output Indoor/Outdoor 3-Way Monitor Loudspeaker with 260mm (10 in) LF and Coaxial Mid-High Frequency Drivers. Extended Bandwidth, Extremely Smooth Response. Full Outdoor Capability (IP-x5). 38 Hz – 17 kHz. 250 Watts, 93 dB Sensitivity. SonicGuard Overload Protection. Included InvisiBall® Hardware Plus Ten 6 mm Attachment Points For Suspension and Optional U-Bracket. Includes 70V/100V Input Line Transformer with Taps at 150W, 75W, and 38W (Plus 19W At 70V only), Plus 4 ohm Bypass Position. Compact at 593 x 372 x 345 mm (23.3 x 14.6 x 13.5 in). 20.3 kg (42 lb).		
CONTROL 30	CONTROL 30		\$	857.85
		High Output Indoor/Outdoor 3-Way Monitor Loudspeaker with 260mm (10 in) LF and Coaxial Mid-High Frequency Drivers. Extended Bandwidth, Extremely Smooth Response. Full Outdoor Capability (IP-x5). 38 Hz – 17 kHz. 250 Watts, 93 dB Sensitivity. SonicGuard Overload Protection. Included InvisiBall® Hardware Plus Ten 6 mm Attachment Points For Suspension and Optional U-Bracket. Includes 70V/100V Input Line Transformer with Taps at 150W, 75W, and 38W (Plus 19W At 70V only), Plus 4 ohm Bypass Position. Compact at 593 x 372 x 345 mm (23.3 x 14.6 x 13.5 in). 20.3 kg (42 lb), in White.		
CONTROL 30-WH	CONTROL 30-WH		\$	857.85
IVX-21608	IVX-21608	Intellivox-HP-DS370 Surcharge Custom Color. Made to Order Call for availability	\$	865.00
JBLCSM32V	JBLCSM32V	3 x 2 Stereo/Mono Public Address Mixer	\$	893.96
		2 x 300W DriveCore Amplifier, Fanless, 8ohm/70V/100V, supports CSR-V volume control, sleep mode (w/ disable), 2U Full-Rack, Mounting kit		
NCSA2300Z-0-US	NCSA2300Z-0-US		\$	898.00
		JBL Packaged PA System with integrated 300 Watt powered mixer; 8-channel mixer with user selectable Reverb on Ch1-4, 2 x 8" JBL two-way speakers, durable plastic enclosure. Weight 38.8lbs.		
EON208P	EON208P		\$	899.00
		Straight Line Array Column with 16 x 2" Drivers and Constant Beamwidth Technology. Switchable 40° or 15° vertical coverage, music (flat)/speech switch, 100W multi-tap transformer or 8 ohms, 80 Hz – 20 kHz, 325W continuous pink noise, 100 cm tall (priced and sold individually) .		
CBT 100LA-1	CBT 100LA-1		\$	920.00
		Straight Line Array Column with 16 x 2" Drivers and Constant Beamwidth Technology. Switchable 40° or 15° vertical coverage, music (flat)/speech switch, 100W multi-tap transformer or 8 ohms, 80 Hz – 20 kHz, 325W continuous pink noise, 100 cm tall (priced and sold individually).		
CBT 100LA-1-WH	CBT 100LA-1-WH		\$	920.00
		Ultra-Compact 2-Way Loudspeaker with 1 x 6.5" LF. 90° x 90° Coverage, Passive. Compact PT™ Progressive Transition™ Waveguide. Suspension Eyebolts Not Included. Optional U-Bracket Model MTU-16.		
AC16	AC16		\$	926.00
AC16-WH	AC16-WH	AC16 in white.	\$	926.00
		4 input - 1 x 120W DriveCore Mixer-Amp, Fanless, 4ohm/8ohm/70V/100V, 1U Half-Rack, Mounting kit		
NCSMA1120-U-US	NCSMA1120-U-US		\$	931.04
		Compact 18" portable subwoofer system; 35Hz Frequency Range, 2400 watt peak power handling, 130dB Max SPL, cloth-backed steel grille M20 pole socket, non-skid rubber feet, Net Weight 33.5kg (74 lbs.)		
PRX418S	PRX418S		\$	936.00
		Dual 15" two-way passive speaker system; 2400 Watt peak power handling , 134dB Maximum SPL , 4 ohms. DuraFlex™-covered 18mm plywood enclosure, 16 gauge cloth-backed steel grille, dual 36 mm pole sockets, non-skid rubber feet. 12 M10 suspension points. Net Weight 33.5kg (74 lbs.)		
PRX425	PRX425		\$	936.00

		12" 2-Way All-Weather Compact Co-axial Loudspeaker. 90° x 90° broadband control, co-ax driver with 300 mm (12 in) Kevlar-reinforced woofer with 75 mm (3 in) voice coil and 25 mm (1 in) compression driver, high-temp polymer diaphragm. Excellent clarity extended frequency response. 400 Watt power handling (1600 W peaks), 55 Hz - 20 kHz frequency range, overload HF protection, 200 Watt 70V/100V multi-tap or direct 8? low-impedance. U-Bracket included. Gray or black (-BK), paintable. Sold and packed as each.		
AWC129	AWC129		\$	945.00
		12" 2-Way All-Weather Compact Co-axial Loudspeaker. 90° x 90° broadband control, co-ax driver with 300 mm (12 in) Kevlar-reinforced woofer with 75 mm (3 in) voice coil and 25 mm (1 in) compression driver, high-temp polymer diaphragm. Excellent clarity extended frequency response. 400 Watt power handling (1600 W peaks), 55 Hz - 20 kHz frequency range, overload HF protection, 200 Watt 70V/100V multi-tap or direct 8? low-impedance. U-Bracket included. Gray or black (-BK), paintable. Sold and packed as each.		
AWC129-BK	AWC129-BK		\$	945.00
AC118S	AC118S	18" Subwoofer with 75mm (3 in) voice coil.	\$	950.00
AC118S-WH	AC118S-WH	AC118S in White	\$	950.00
IVX-802120	IVX-802120	Intellivox Cable entry cover box 6x XLR, pre-assembled, RAL9010. Made to Order Call for availability	\$	966.00
EON618S	EON618S	Powered 18" subwoofer, 1000W class D ampfier with maximum 132dB SPL, Bluetooth control.	\$	999.00
		Powered, 1500W, 12" two-way, bass-reflex system with monitor angle, WiFi capability in a wood cabinet, dual pole mount, M10 suspension points. 135db SPL peak with a 90° x 50° nominal coverage pattern, user-selectable DSP that includes EQ.		
PRX812W	PRX812W		\$	999.00
		Intonato Desktop Controller. Accessory for use with Intonato 24. Large master Volume Control, MUTE, DIM and Keys that provide instant access to Intonato 24 functions including individual speaker MUTE, SOLO, SCENES, TALKBACK and more. Compact desktop form-factor 2.84" (H) x 6.73" (L) x 4.70" (W)72.0mm (H) 117.0mm (L) x 119.4mm (W). Connections: CAT5, RJ45 connector. Power Requirements: Power Over Ethernet (POE supply, CAT5 cable not included).		
INTONATO-DC-M	INTONATO-DC-M		\$	1,000.00
NCSMA280-U-US	NCSMA280-U-US	8 input - 2 x 80W DriveCore Mixer-Amp, Fanless,	\$	1,015.16
AC115S	AC115S	4ohm/8ohm/70V/100V, 1U Full-Rack, Mounting kit	\$	1,020.00
AC266	AC266	15" Subwoofer with 75mm (3 in) voice coil.	\$	1,020.00
AC266-WH	AC266-WH	AC266 in White	\$	1,020.00
AC299	AC299	12" 2-way system, 60° x 60° waveguide coverage pattern with 2408H-2 25mm (1 in) exit, 38mm (1.5 in) voice coil.	\$	1,020.00
AC299-WH	AC299-WH	AC299 in White	\$	1,020.00
		(EN54 Life/Safety) Straight Line Array Column with 16 x 2" Drivers and Constant Beamwidth Technology. Switchable 40° or 15° vertical coverage, music (flat)/speech switch, 100W multi-tap transformer or 8 ohms, 80 Hz – 20 kHz, 325W continuous pink noise, 100 cm tall (priced and sold individually).		
CBT 100LA-LS	CBT 100LA-LS		\$	1,030.40

		(EN54 Life/Safety) Straight Line Array Column with 16 x 2" Drivers and Constant Beamwidth Technology. Switchable 40° or 15° vertical coverage, music (flat)/speech switch, 100W multi-tap transformer or 8 ohms, 80 Hz – 20 kHz, 325W continuous pink noise, 100 cm tall (priced and sold individually)		
CBT 100LA-LS-WH	CBT 100LA-LS-WH	New in -1 version: Included wall bracket adjusts for SWIVEL (pan) as well as tilt aiming, for increased aiming versatility.	\$	1,030.40
VRX-AF-II	VRX-AF	Array Frame for suspending VRX932LA-1/P, VRX918S/P enclosures. Includes 4 x Quick Release Pins, 2 x Shackles, 2 x Drop Levers	\$	1,049.00
PRX815W	PRX815W	Powered, 1500W, 15" two-way, bass-reflex system with monitor angle, WiFi capability in a wood cabinet, dual pole mount, M10 suspension points. 137db SPL peak with a 90° x 50° nominal coverage pattern, user-selectable DSP that includes EQ.	\$	1,099.00
AWC15LF-BK	AWC15LF-BK	15" All-Weather Compact Low Frequency Loudspeaker. 380 mm (15 in) Kevlar-reinforced cone with 75 mm (3 in) voice coil. Designed to extend low frequency response of a sound system. 500 Watt power handling (2000 W peaks), 45 Hz - 2.2 kHz frequency range, 300 Watt 70V/100V multi-tap or direct 8 ohm low-impedance. U-Bracket included. Gray or black (-BK), paintable. Sold and packed as each.	\$	1,100.00
AWC15LF	AWC15LF	15" All-Weather Compact Low Frequency Loudspeaker. 380 mm (15 in) Kevlar-reinforced cone with 75 mm (3 in) voice coil. Designed to extend low frequency response of a sound system. 500 Watt power handling (2000 W peaks), 45 Hz - 2.2 kHz frequency range, 300 Watt 70V/100V multi-tap or direct 8 ohm low-impedance. U-Bracket included. Gray or black (-BK), paintable. Sold and packed as each.	\$	1,100.00
NCSMA2120-U-US	NCSMA2120-U-US	8 input - 2 x 120W DriveCore Mixer-Amp, Fanless, 4ohm/8ohm/70V/100V, 1U Full-Rack, Mounting kit	\$	1,117.06
SRX812	SRX812	SRX812 is a two-way full range speaker with a 12" woofer made for use as a light duty main PA, monitor, or rear or side fill. Premium utility hardware makes SRX812 an ideal solution for sound reinforcement. Tunings for Crown amps and dbx processors are available at jblpro.com	\$	1,124.00
AC18/26	AC18/26	Compact 2-Way Loudspeaker with 1 x 8" LF. 120° x 60° Coverage, Passive. Compact PT™ Progressive Transition™ Waveguide, Rotatable. Suspension Eyebolts Not Included. Optional U-Bracket Model MTU-18.	\$	1,134.00
AC18/26-WH	AC18/26-WH	AC18/26 in white.	\$	1,134.00
AC18/95	AC18/95	Compact 2-Way Loudspeaker with 1 x 8" LF. 90° x 50° Coverage, Passive. Compact PT™ Progressive Transition™ Waveguide, Rotatable. Suspension Eyebolts Not Included. Optional U-Bracket Model MTU-18.	\$	1,134.00
AC18/95-WH	AC18/95-WH	AC18/95 in white.	\$	1,134.00
AC566	AC566	15" 2-way system, 60° x 60° waveguide coverage pattern with 2408H-2 25mm (1 in) exit, 38mm (1.5 in) voice coil.	\$	1,140.00
AC566-WH	AC566-WH	AC566 in White	\$	1,140.00
AC599	AC599	15" 2-way system, 90° x 90° waveguide coverage pattern with 2408H-2 25mm (1 in) exit, 38mm (1.5 in) voice coil.	\$	1,140.00
AC599-WH	AC599-WH	AC299 in White	\$	1,140.00
AC2212/64	AC2212/64	Compact 2-Way Loudspeaker with 1 x 12" LF. 60° x 40° Coverage, Bi-Amp/Passive Switchable. Compact PT™ Progressive Transition™ Waveguide. Suspension Eyebolts Not Included. Optional U-Bracket Model MTU-4.	\$	1,172.00

AC2212/64-WH	AC2212/64-WH	Compact 2-Way Loudspeaker with 1 x 12" LF. 60° x 40° Coverage, Bi-Amp/Passive Switchable. Compact PT™ Progressive Transition™ Waveguide. Suspension Eyebolts Not Included. Optional U-Bracket Model MTU-4.	\$	1,172.00
AC2212/95	AC2212/95	Compact 2-Way Loudspeaker with 1 x 12" LF. 90° x 50° Coverage, Bi-Amp/Passive Switchable. Compact PT™ Progressive Transition™ Waveguide. Suspension Eyebolts Not Included. Optional U-Bracket Model MTU-4.	\$	1,172.00
AC2212/95-WH	AC2212/95-WH	Compact 2-Way Loudspeaker with 1 x 12" LF. 90° x 50° Coverage, Bi-Amp/Passive Switchable. Compact PT™ Progressive Transition™ Waveguide. Suspension Eyebolts Not Included. Optional U-Bracket Model MTU-4.	\$	1,172.00
AC2212/00	AC2212/00	Compact 2-Way Loudspeaker with 1 x 12" LF. 100° x 100° Coverage, Bi-Amp/Passive Switchable. Compact PT™ Progressive Transition™ Waveguide. Suspension Eyebolts Not Included. Optional U-Bracket Model MTU-4. Optional Planar Array Frame Kit PAF-2K 3 Wide Array With ASB6118 Subwoofer Center.	\$	1,228.00
EON ONE	EON ONE	A linear-array P.A. system that brings an unobstructed 10" bass reflex subwoofer with 6 - 2" drivers. The built-in 6-channel mixer provides a combination of XLR, 1/4", 3.5mm, RCA, and Bluetooth audio into a true all-in-one design that you can carry with one hand. Weight 40.8lbs.	\$	1,249.00
SRX815	SRX815	SRX815 is a two-way full range speaker with a 15" woofer made for use as a light to medium duty main PA, monitor, or rear or side fill. Premium utility hardware makes SRX815 an ideal solution for sound reinforcement. Tunings for Crown amps and dbx processors are available at jblpro.com	\$	1,249.00
705P	705P	JBL 7-Series 705P 5-inch Bi-Amplified Master Reference Studio Monitor, with 725G five-inch low frequency transducer, 2409H HF transducer, and patented Image Control Waveguide. Dual Class-D Power Amplifiers with 250 Watts for LF and 250 Watts for HF. Digital and Analog Inputs. Integrated Room and User EQ.	\$	1,249.00
AC2215/64	AC2215/64	Compact 2-Way Loudspeaker with 1 x 15" LF. 60° x 40° Coverage, Bi-Amp/Passive Switchable. Compact PT™ Progressive Transition™ Waveguide. Suspension Eyebolts Not Included. Optional U-Bracket Model MTU-2.	\$	1,278.00
AC2215/64-WH	AC2215/64-WH	Compact 2-Way Loudspeaker with 1 x 15" LF. 60° x 40° Coverage, Bi-Amp/Passive Switchable. Compact PT™ Progressive Transition™ Waveguide. Suspension Eyebolts Not Included. Optional U-Bracket Model MTU-2. White finish.	\$	1,278.00
AC2215/95	AC2215/95	Compact 2-Way Loudspeaker with 1 x 15" LF. 90° x 50° Coverage, Bi-Amp/Passive Switchable. Compact PT™ Progressive Transition™ Waveguide. Suspension Eyebolts Not Included. Optional U-Bracket Model MTU-2.	\$	1,278.00
AC2215/95-WH	AC2215/95-WH	Compact 2-Way Loudspeaker with 1 x 15" LF. 90° x 50° Coverage, Bi-Amp/Passive Switchable. Compact PT™ Progressive Transition™ Waveguide. Suspension Eyebolts Not Included. Optional U-Bracket Model MTU-2. White finish.	\$	1,278.00
CBT 70J-1	CBT 70J-1	70 cm J-Shaped Coaxial Line Array with 16 x 1" and 4 x 5" Drivers and Asymmetrical Coverage. Constant Beamwidth Technology, switchable 45° or 25° vertical coverage, music (flat)/speech switch, 8 ohms, 60 Hz – 20 kHz, 500W cont pink (2000W peak), wall bracket included. (priced and sold individually). New in -1 version: Included wall bracket adjusts for SWIVEL (pan) as well as tilt aiming, for increased aiming versatility. Thicker, stronger grille which is more robust for use in temporary special event applications.	\$	1,296.66

CBT 70J-1-WH	CBT 70J-1-WH	70 cm J-Shaped Coaxial Line Array with 16 x 1" and 4 x 5" Drivers and Asymmetrical Coverage. Constant Beamwidth Technology, switchable 45° or 25° vertical coverage, music (flat)/speech switch, 8 ohms, 60 Hz – 20 kHz, 500W cont pink (2000W peak), wall bracket included. (priced and sold individually). New in -1 version: Included wall bracket adjusts for SWIVEL (pan) as well as tilt aiming, for increased aiming versatility. Thicker, stronger grille which is more robust for use in temporary special event applications.	\$	1,296.66
AC26	AC26	Compact 2-Way Loudspeaker with 2 x 6.5" LF. 90° x 90° Coverage, Passive. Compact PT™ Progressive Transition™ Waveguide. Suspension Eyebolts Not Included. Optional U-Bracket Model MTU-26.	\$	1,324.00
AC26-WH	AC26-WH	AC26 in white.	\$	1,324.00
AC2215/00	AC2215/00	Compact 2-Way Loudspeaker with 1 x 15" LF. 100° x 100° Coverage, Bi-Amp/Passive Switchable. Compact PT™ Progressive Transition™ Waveguide. Suspension Eyebolts Not Included. Optional U-Bracket Model MTU-2.	\$	1,324.00
AC2212/00-WH	AC2212/00-WH	Compact 2-Way Loudspeaker with 1 x 12" LF. 100° x 100° Coverage, Bi-Amp/Passive Switchable. Compact PT™ Progressive Transition™ Waveguide. Suspension Eyebolts Not Included. Optional U-Bracket Model MTU-4.	\$	1,342.00
PRX815XLFW	PRX815XLFW	Powered, 1500W, 15" extended low frequency subwoofer with WiFi capability in a wood cabinet, dual pole mount, M20 threaded pole socket. 134 db SPL with dbx Type IV Limiter circuit.	\$	1,399.00
CBT 1000E	CBT 1000E	Extension for CBT 1000 Line Array, six (6) 165 mm (6-1/2") high-excursion LF drivers, 1500W cont pink noise (6000 W peak), 8 ohms (note CBT1000+1000E is a 4 ohm system), linking coupler bracket included, 100 cm tall for 200 cm tall CBT 1000+E array, connect CBT1000 and CBT1000E in parallel. Combined with CBT 1000, system response is 38 Hz – 20 kHz with well controlled pattern to 200 Hz. (priced and sold individually).	\$	1,450.00
CBT 1000E-WH	CBT 1000E-WH	Extension for CBT 1000 Line Array. Same as CBT1000E, in white. (priced and sold individually).	\$	1,450.00
AWC159	AWC159	15" 2-Way All-Weather Compact Co-axial Loudspeaker. 90° x 90° broadband control, co-ax driver with 380 mm (15 in) Kevlar-reinforced woofer with 75 mm (3 in) voice coil and 38 mm (1.5 in) compression driver, high-temp polymer diaphragm. Excellent clarity extended frequency response. 500 Watt power handling (2000 W peaks), 52 Hz - 20 kHz frequency range, 300 Watt 70V/100V multi-tap or direct 8 ohm low-impedance. U-Bracket included. Gray or black (-BK), paintable. Sold and packed as each.	\$	1,450.00
AWC159-BK	AWC159-BK	15" 2-Way All-Weather Compact Co-axial Loudspeaker. 90° x 90° broadband control, co-ax driver with 380 mm (15 in) Kevlar-reinforced woofer with 75 mm (3 in) voice coil and 38 mm (1.5 in) compression driver, high-temp polymer diaphragm. Excellent clarity extended frequency response. 500 Watt power handling (2000 W peaks), 52 Hz - 20 kHz frequency range, 300 Watt 70V/100V multi-tap or direct 8 ohm low-impedance. U-Bracket included. Gray or black (-BK), paintable. Sold and packed as each.	\$	1,450.00
PRX818XLFW	PRX818XLFW	Powered, 1500W, 18" extended low frequency subwoofer with WiFi capability in a wood cabinet, dual pole mount, M20 threaded pole socket. 134 db SPL with dbx Type IV Limiter circuit.	\$	1,499.00

SRX818S is a single 18" subwoofer for concert, touring, or installed use, featuring a standard M20 pole cup for use with top boxes, indexing feet for stacking in both standard and cardioid position, and a 136dB max SPL. Tunings for Crown amps and dbx processors are available at jblpro.com

SRX818S	SRX818S	Compact high output two-way externally powered studio monitor with 728G eight-inch (203 mm) high-excursion differential driver low frequency transducer and 2409H high-frequency compression driver; Patent-pending Image Control Waveguide provides a seamless crossover transition and detailed imaging. 35Hz - 36 kHz frequency range; 114dB Maximum Peak SPL; Dividing Network Transition Frequency: 1.7 kHz. Dividing Network can be bypassed for bi-amplified operation. Birch Plywood enclosure includes rear and bottom mounting points; Not intended for stand-alone use. Complete system requires HARMAN Professional signal processor and external Crown Power Amplifier (not Included.)	\$	1,499.00
LSR708i	LSR708i	Compact 2-Way Loudspeaker with 1 x 15" LF. 100° x 100° Coverage, Bi-Amp/Passive Switchable. Compact PT™ Progressive Transition™ Waveguide. Suspension Eyebolts Not Included. Optional U-Bracket Model MTU-2. White finish.	\$	1,500.00
AC2215/00-WH	AC2215/00-WH	Compact 2-Way Loudspeaker with 2 x 8" LF. 120° x 60° Coverage, Passive. Compact PT™ Progressive Transition™ Waveguide, Rotatable. Suspension Eyebolts Not Included.	\$	1,512.00
AC28/26	AC28/26	Optional U-Bracket Model MTU-28.	\$	1,530.00
AC28/26-WH	AC28/26-WH	AC28/26 in white.	\$	1,530.00
AC28/95	AC28/95	Compact 2-Way Loudspeaker with 2 x 8" LF. 90° x 50° Coverage, Passive. Compact PT™ Progressive Transition™ Waveguide, Rotatable. Suspension Eyebolts Not Included. Optional U-Bracket Model MTU-28.	\$	1,530.00
AC28/95-WH	AC28/95-WH	AC28/95 in white.	\$	1,530.00
VRX915S	VRX915S	15" Bass Reflex Subwoofer	\$	1,549.00
VRX915S-WH	VRX915S-WH	15" Bass Reflex Subwoofer - white	\$	1,549.00
AM5212/95-WH	AM5212/95-WH	Medium Power 12" 2-Way Full-Range Loudspeaker System with JBL Differential Drive® 50.8 mm (2-in) dual voice coil and dual magnetic gap 262H low frequency driver and 2408H-1 high-frequency 38mm (1.5 in) exit, 38mm (1.5 in) voice-coil compression driver. 90° x 50° rotatable Progressive Transition™ waveguide, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Optional U-bracket model MTU-3. White finish.	\$	1,596.00
PRX825W	PRX825W	Powered, 1500W, dual 15" two-way, bass-reflex system with WiFi capability in a wood cabinet, dual pole mount, M10 suspension points. 138db SPL peak with a 90° x 50° nominal coverage pattern, user-selectable DSP that includes EQ.	\$	1,599.00
PRX835W	PRX835W	Powered, 1500W, 15" three-way, full-range system with WiFi capability in a wood cabinet, dual pole mount, M10 suspension points. 138db SPL peak with a 90° x 50° nominal coverage pattern, user-selectable DSP that includes EQ.	\$	1,599.00
SRX812P	SRX812P	2000 Watt Powered 2-way system featuring Crown Amplification, network control, and full user configurable DSP. The SRX812P can be used as either a monitor or a main system and features M10 suspension points for easy rigging. Full suite of onboard DSP includes 20 PEQs, 96kHz FIR filters, signal generators, and 2 seconds of delay.	\$	1,623.00
EON One PRO	EON One PRO		\$	1,623.75

SRX835 is a three-way full range speaker with a 15" woofer made for use as a medium duty main PA, or rear or side fill. Premium utility hardware makes SRX835 an ideal solution for sound reinforcement. Tunings for Crown amps and dbx processors are available at jblpro.com

SRX835	SRX835		\$	1,624.00
		Ultra Compact High-Power 12" Subwoofer System. 2263H Differential Drive® woofer, 3" dual voice coil – dual gap, neodymium magnet. Multiply hardwood enclosure with DuraFlex™ finish and 14-gauge steel grille. Sixteen M10 suspension points. Available in Black or White. Priced as each.		
ASB6112	ASB6112		\$	1,638.00
		Ultra Compact High-Power 12" Subwoofer System. 2263H Differential Drive® woofer, 3" dual voice coil – dual gap, neodymium magnet. Multiply hardwood enclosure with DuraFlex™ finish and 14-gauge steel grille. Sixteen M10 suspension points. White finish. Priced as each.		
ASB6112-WH	ASB6112-WH		\$	1,638.00
		18" compact, flying subwoofer; 2268H Differential Drive® LF; integral flying hardware compatible with VRX932LA-1 and accessories; handles and pole mount deleted. Black DuraFlex™ finish.		
VRX918S	VRX918S		\$	1,679.00
		18" Compact, Flying Subwoofer; 2268H Differential Drive® LF; Integral Flying Hardware Compatible with VRX932LA and Accessories; Designed for Fixed Installations with JBL's White Duraflex™; No Pole Mount or Handles Included.		
VRX918S-WH	VRX918S-WH		\$	1,679.00
		Medium Power 15" 2-Way Full-Range Loudspeaker System with JBL Differential Drive® 50.8 mm (2-in) dual voice coil and dual magnetic gap 265H low frequency driver and 2408H-1 high-frequency 38mm (1.5 in) exit, 38mm (1.5 in) voice-coil compression driver. 60° x 60° rotatable Progressive Transition™ waveguide, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Optional U-bracket model MTU-1.		
AM5215/66	AM5215/66		\$	1,685.00
		Medium Power 15" 2-Way Full-Range Loudspeaker System with JBL Differential Drive® 50.8 mm (2-in) dual voice coil and dual magnetic gap 265H low frequency driver and 2408H-1 high-frequency 38mm (1.5 in) exit, 38mm (1.5 in) voice-coil compression driver. 60° x 60° rotatable Progressive Transition™ waveguide, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Optional U-bracket model MTU-1. White finish.		
AM5215/66-WH	AM5215/66-WH		\$	1,685.00
		2000 Watt Powered 2-way system featuring Crown Amplification, network control, and full user configurable DSP. The SRX815P can be used as either a monitor or a main system and features M10 suspension points for easy rigging. Full suite of onboard DSP includes 20 PEQs, 96kHz FIR filters, signal generators, and 2 seconds of delay.		
SRX815P	SRX815P		\$	1,748.00
		8" two-way line-array system with 1 x 2168H-1 Differential Drive® 400 W LF; 2 x 2414H 1 inch compression driver HF on Constant Curvature waveguide; dual angle pole socket and integral rigging hardware; passive or bi-amplified operation. Black DuraFlex™ finish.		
VRX928LA	VRX928LA		\$	1,779.00
		8" Two-Way Line-Array System with 1 x 2168H-1 Differential Drive® 400W LF; 2 x 2414H 1 inch Compression Driver HF on Constant Curvature Waveguide; Dual Angle Pole Socket and Integral Rigging Hardware; Passive or Bi-Amplified Operation. White DuraFlex™ Finish.		
VRX928LA-WH	VRX928LA-WH		\$	1,779.00

Compact High-Power 15" Subwoofer System. 2265H-1 Differential Drive® woofer, 3" dual voice coil – dual gap, neodymium magnet. Multiply hardwood enclosure with DuraFlex™ finish and 14-gauge steel grille. Sixteen M10 suspension points. Available in Black and White. Priced as each.

ASB6115	ASB6115		\$	1,852.00
		Compact High-Power 15" Subwoofer System. 2265H-1 Differential Drive® woofer, 3" dual voice coil – dual gap, neodymium magnet. Multiply hardwood enclosure with DuraFlex™ finish and 14-gauge steel grille. Sixteen M10 suspension points. Priced as each.	\$	1,852.00
ASB6115-WH	ASB6115-WH		\$	1,852.00
		High Power 1 x 15" Low Frequency Loudspeaker. 1 x 15" 2265H Differential Drive® woofer. Available in Black or White (-WH). Priced as each. Suspension Eyebolts Not Included. Arrays With AM7200 and Mid-High Loudspeakers using PAF-3K Planar Array Frame Kit.	\$	1,852.00
AL7115	AL7115		\$	1,852.00
		High Power 1 x 15" Low Frequency Loudspeaker. 1 x 15" 2265H Differential Drive® woofer. Available in Black or White (-WH). Priced as each. Suspension Eyebolts Not Included. Arrays With AM7200 and Mid-High Loudspeakers using PAF-3K Planar Array Frame Kit.	\$	1,852.00
AL7115-WH	AL7115-WH		\$	1,852.00
IVX-576125	IVX-576125	Intellivox V-90 MKII, Ral 9007 - EN54:24. Made to Order. Made to Order Call for availability	\$	1,890.00
IVX-577125	IVX-577125	Intellivox V-90 MKII, Ral 9010 - EN54:24. Made to Order Call for availability	\$	1,890.00
		Medium Power 12" 2-Way Full-Range Loudspeaker System with JBL Differential Drive® 50.8 mm (2-in) dual voice coil and dual magnetic gap 262H low frequency driver and 2408H-1 high-frequency 38mm (1.5 in) exit, 38mm (1.5 in) voice-coil compression driver. 100° x 100° rotatable Progressive Transition™ waveguide, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Optional U-bracket model MTU-3.	\$	1,916.00
AM5212/00	AM5212/00		\$	1,916.00
		Medium Power 12" 2-Way Full-Range Loudspeaker System with JBL Differential Drive® 50.8 mm (2-in) dual voice coil and dual magnetic gap 262H low frequency driver and 2408H-1 high-frequency 38mm (1.5 in) exit, 38mm (1.5 in) voice-coil compression driver. 100° x 100° rotatable Progressive Transition™ waveguide, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Optional U-bracket model MTU-3. White finish.	\$	1,916.00
AM5212/00-WH	AM5212/00-WH		\$	1,916.00
		Medium Power 12" 2-Way Full-Range Loudspeaker System with JBL Differential Drive® 50.8 mm (2-in) dual voice coil and dual magnetic gap 262H low frequency driver and 2408H-1 high-frequency 38mm (1.5 in) exit, 38mm (1.5 in) voice-coil compression driver. 120° x 60° rotatable Progressive Transition™ waveguide, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Optional U-bracket model MTU-3. White finish.	\$	1,916.00
AM5212/26	AM5212/26		\$	1,916.00
		Medium Power 12" 2-Way Full-Range Loudspeaker System with JBL Differential Drive® 50.8 mm (2-in) dual voice coil and dual magnetic gap 262H low frequency driver and 2408H-1 high-frequency 38mm (1.5 in) exit, 38mm (1.5 in) voice-coil compression driver. 120° x 60° rotatable Progressive Transition™ waveguide, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Optional U-bracket model MTU-3. White finish.	\$	1,916.00
AM5212/26-WH	AM5212/26-WH		\$	1,916.00

		Medium Power 12" 2-Way Full-Range Loudspeaker System with JBL Differential Drive® 50.8 mm (2-in) dual voice coil and dual magnetic gap 262H low frequency driver and 2408H-1 high-frequency 38mm (1.5 in) exit, 38mm (1.5 in) voice-coil compression driver. 60° x 40° rotatable Progressive Transition™ waveguide, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Optional U-bracket model MTU-3.		
AM5212/64	AM5212/64		\$	1,916.00
		Medium Power 12" 2-Way Full-Range Loudspeaker System with JBL Differential Drive® 50.8 mm (2-in) dual voice coil and dual magnetic gap 262H low frequency driver and 2408H-1 high-frequency 38mm (1.5 in) exit, 38mm (1.5 in) voice-coil compression driver. 60° x 40° rotatable Progressive Transition™ waveguide, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Optional U-bracket model MTU-3. White finish.		
AM5212/64-WH	AM5212/64-WH		\$	1,916.00
		Medium Power 12" 2-Way Full-Range Loudspeaker System with JBL Differential Drive® 50.8 mm (2-in) dual voice coil and dual magnetic gap 262H low frequency driver and 2408H-1 high-frequency 38mm (1.5 in) exit, 38mm (1.5 in) voice-coil compression driver. 60° x 60° rotatable Progressive Transition™ waveguide, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Optional U-bracket model MTU-3.		
AM5212/66	AM5212/66		\$	1,916.00
		Medium Power 12" 2-Way Full-Range Loudspeaker System with JBL Differential Drive® 50.8 mm (2-in) dual voice coil and dual magnetic gap 262H low frequency driver and 2408H-1 high-frequency 38mm (1.5 in) exit, 38mm (1.5 in) voice-coil compression driver. 60° x 60° rotatable Progressive Transition™ waveguide, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Optional U-bracket model MTU-3. White finish.		
AM5212/66-WH	AM5212/66-WH		\$	1,916.00
		Medium Power 12" 2-Way Full-Range Loudspeaker System with JBL Differential Drive® 50.8 mm (2-in) dual voice coil and dual magnetic gap 262H low frequency driver and 2408H-1 high-frequency 38mm (1.5 in) exit, 38mm (1.5 in) voice-coil compression driver. 90° x 50° rotatable Progressive Transition™ waveguide, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Optional U-bracket model MTU-3.		
AM5212/95	AM5212/95		\$	1,916.00
IVX-576126	IVX-576126	Intellivox H-90 MKII Symmetric Dir Cntl, Ra1 9007 - EN54:24. Made to Order Call for availability	\$	1,983.00
IVX-577126	IVX-577126	Intellivox H-90 MKII Symmetric Directivity Control, Ra1 9010 - EN54:24. Made to Order Call for availability	\$	1,983.00
AC18/95-WRC	AC18/95-WRC	Ultra-Compact 2-Way Loudspeaker with 1 x 5.25" LF. 90° x 90° Coverage, Passive. Suspension Eyebolts Not Included. Optional U-Bracket Model MTU-15. Sold as 2 per carton.	\$	1,984.00
VLA-C-SB	VLA-C-SB	Suspension Kit for VLA-C Arrays with 2 pcs VLA-C-SB Suspension Bars (for top and bottom of array) and 4 pcs ¾" Drop-Forged Anchor Shackles. See user's guide for instructions and limitations. Black only.	\$	1,995.00

SRX835P	SRX835P	2000 Watt Powered 3-way system featuring Crown Amplification, network control, and full user configurable DSP. The SRX835P can be pole mounted or stacked and splayed atop a subwoofer, and features M10 suspension points for easy rigging. Full suite of onboard DSP includes 20 PEQs, 96kHz FIR filters, signal generators, and 2 seconds of delay.	\$	1,998.00
SRX818SP	SRX818SP	1000 Watt Powered 18" subwoofer featuring Crown Amplification, network control, and full user configurable DSP. The SRX818SP provides extended low frequency for any system, and features M10 suspension points for easy rigging. Full suite of onboard DSP includes 20 PEQs, 96kHz FIR filters, signal generators, and 2 seconds of delay.	\$	1,998.00
SRX828S	SRX828S	SRX828S is a dual 18" subwoofer for concert, touring, or installed use, featuring a wide stance for splaying top boxes, indexing feet for stacking in both the standard and cardioid position, and a 141dB max SPL. Tunings for Crown amps and dbx processors are available at jblpro.com	\$	1,999.00
AM5215/26	AM5215/26	Medium Power 15" 2-Way Full-Range Loudspeaker System with JBL Differential Drive® 50.8 mm (2-in) dual voice coil and dual magnetic gap 265H low frequency driver and 2408H-1 high-frequency 38mm (1.5 in) exit, 38mm (1.5 in) voice-coil compression driver. 120° x 60° rotatable Progressive Transition™ waveguide, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Optional U-bracket model MTU-1.	\$	2,022.00
AM5215/26-WH	AM5215/26-WH	Medium Power 15" 2-Way Full-Range Loudspeaker System with JBL Differential Drive® 50.8 mm (2-in) dual voice coil and dual magnetic gap 265H low frequency driver and 2408H-1 high-frequency 38mm (1.5 in) exit, 38mm (1.5 in) voice-coil compression driver. 120° x 60° rotatable Progressive Transition™ waveguide, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Optional U-bracket model MTU-1. White finish.	\$	2,022.00
AM5215/64	AM5215/64	Medium Power 15" 2-Way Full-Range Loudspeaker System with JBL Differential Drive® 50.8 mm (2-in) dual voice coil and dual magnetic gap 265H low frequency driver and 2408H-1 high-frequency 38mm (1.5 in) exit, 38mm (1.5 in) voice-coil compression driver. 60° x 40° rotatable Progressive Transition™ waveguide, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Optional U-bracket model MTU-1.	\$	2,022.00
AM5215/64-WH	AM5215/64-WH	Medium Power 15" 2-Way Full-Range Loudspeaker System with JBL Differential Drive® 50.8 mm (2-in) dual voice coil and dual magnetic gap 265H low frequency driver and 2408H-1 high-frequency 38mm (1.5 in) exit, 38mm (1.5 in) voice-coil compression driver. 60° x 40° rotatable Progressive Transition™ waveguide, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Optional U-bracket model MTU-1. White finish.	\$	2,022.00

		Medium Power 15" 2-Way Full-Range Loudspeaker System with JBL Differential Drive® 50.8 mm (2-in) dual voice coil and dual magnetic gap 265H low frequency driver and 2408H-1 high-frequency 38mm (1.5 in) exit, 38mm (1.5 in) voice-coil compression driver. 90° x 50° rotatable Progressive Transition™ waveguide, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Optional U-bracket model MTU-1.		
AM5215/95	AM5215/95		\$	2,022.00
		Medium Power 15" 2-Way Full-Range Loudspeaker System with JBL Differential Drive® 50.8 mm (2-in) dual voice coil and dual magnetic gap 265H low frequency driver and 2408H-1 high-frequency 38mm (1.5 in) exit, 38mm (1.5 in) voice-coil compression driver. 90° x 50° rotatable Progressive Transition™ waveguide, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Optional U-bracket model MTU-1. White finish.		
AM5215/95-WH	AM5215/95-WH		\$	2,022.00
		15" two-way dedicated floor monitor system with an 800 watt 2265H Differential Drive® LF; 2452H, 4" voice coil compression driver, 50 x 90 waveguide; passive or bi-amplified operation; compact 30° symmetrical wedge enclosure; Black DuraFlex™ finish; heavy duty 16 gauge foam backed steel grille.		
VRX915M	VRX915M		\$	2,059.00
		Subcompact System Short Frame for suspension of VT4886 arrays. Mates to integrated suspension hardware on VT4886. Can also be used for ground stacking. Machined Aluminum with Graded Assembly Hardware. Aluminum Receiver Blocks and Steel Quick Release Pins with Restraining Lanyards. An attachment point for Bottom-array. Weight 5.8 kg (12.8 lb). Black.		
VT4886-SF	VT4886-SF		\$	2,096.64
		200 cm (6.6 ft) Tall Constant Beamwidth Technology™ Line Array Column with Thirty-Two 50 mm (2 in) Drivers. Patented CBT Technology for true constant directivity & reduced lobing. Extended pattern control. Selectable vertical pattern – 30° or 15° for medium or long-throw. Asymmetrical Progressive-Gradient vertical coverage setting directs more sound toward far areas. Dynamic Sonic-Guard™ low-audibility overload protection. Swivel (pan) / tilt wall bracket included 70V/100V transformer (each module, for 120W + 120W), plus direct capability. Available black or white (-WH). Sold and packed as each -- carton includes top and bottom speaker modules and coupling plate, which comprise one CBT 200LA-1 column, plus wall bracket		
CBT 200LA-1	CBT 200LA-1		\$	2,150.00
		200 cm (6.6 ft) Tall Constant Beamwidth Technology™ Line Array Column with Thirty-Two 50 mm (2 in) Drivers. Patented CBT Technology for true constant directivity & reduced lobing. Extended pattern control. Selectable vertical pattern – 30° or 15° for medium or long-throw. Asymmetrical Progressive-Gradient vertical coverage setting directs more sound toward far areas. Dynamic Sonic-Guard™ low-audibility overload protection. Swivel (pan) / tilt wall bracket included 70V/100V transformer (each module, for 120W + 120W), plus direct capability. Available black or white (-WH). Sold and packed as each -- carton includes top and bottom speaker modules and coupling plate, which comprise one CBT 200LA-1 column, plus wall bracket		
CBT 200LA-1-WH	CBT 200LA-1-WH		\$	2,150.00
IVX-577135	IVX-577135	Intellivox V-90 MKII, Special Color] - EN54:24. Made to Order Call for availability	\$	2,299.00

IVX-577136	IVX-577136	Intellivox H-90 MKII, Special Color] - EN54:24. Made to Order Call for availability	\$	2,299.00
ASB6118	ASB6118	High Power Single 18" Subwoofer. 1 x 18" 2242H VGC™ Driver. Suspension Eyebolts Not Included. Arrays with AM6200 and AM4200 Mid-High Loudspeakers Using Optional PAF-2K Planar Array Frame Kit. Priced as each.	\$	2,388.00
ASB6118-WH	ASB6118-WH	High Power Single 18" Subwoofer. 1 x 18" 2242H VGC™ Driver. Suspension Eyebolts Not Included. Arrays with AM6200 and AM4200 Mid-High Loudspeakers Using Optional PAF-2K Planar Array Frame Kit. White finish. Priced as each.	\$	2,388.00
VRX918SP	VRX918SP	Powered 18" flying subwoofer; 2268H Differential Drive® LF, Crown DPC-2 Amplifier Module with system DSP; Integral Rigging Hardware Compatible with VRX932LAP; Top Mounted M20 Threaded Pole Socket; Black DuraFlex™ finish.	\$	2,399.00
SRX828SP	SRX828SP	2000 Watt Powered dual 18" subwoofer featuring Crown Amplification, network control, and full user configurable DSP. The SRX828SP provides extended low frequency for any system, and features M10 suspension points for easy rigging. Full suite of onboard DSP includes 20 PEQs, 96kHz FIR filters, signal generators, and 2 seconds of delay.	\$	2,498.00
708P	708P	JBL 7-Series 708P 8-inch Bi-Amplified Master Reference Studio Monitor, with 728G eight-inch Differential Drive (tm) low-frequency transducer, 2409H HF transducer, and patented Image Control Waveguide. Dual Class-D Power Amplifiers with 250 Watts for LF and 250 Watts for HF. Digital and Analog Inputs. Integrated Room and User EQ.	\$	2,499.00
PD525S	PD525S	Dual 15" subwoofer system, 2275H driver, 75mm (3 in) voice coil, 4-ohm nominal impedance.	\$	2,568.00
PD525S - WH	PD525S - WH	Dual 15" subwoofer system, 2275H driver, 75mm (3 in) voice coil, 4-ohm nominal impedance.	\$	2,568.00
VT4886-AF	VT4886-AF	Subcompact System Array Frame for suspension of VT4883, VT4886 or mixed VT4883/VT4886 arrays. Mates to integrated suspension hardware on both models. Can also be used for ground stacking. Machined Aluminum with Graded Assembly Hardware. Receiver Blocks and Steel Quick Release Pins with Restraining Lanyards. Black.	\$	2,595.84
CBT 1000	CBT 1000	High-Output Two-Way Line Array Column with Highly Adjustable Vertical Coverage and Tapered Horizontal Waveguide. Six (6) 165 mm (6-1/2 in) high-excursion LF drivers and twenty-four (24) 25 mm (1 in) extra-high-power soft dome tweeters. .Constant Beamwidth Technology, switchable between 4 "pattern up" and 4 "pattern down" vertical coverages (for total of 16 settings, music (flat)/speech switch, 4 ohms, 45 Hz – 20 kHz, 1500W cont pink (6000W peak), two-part wall bracket included. Black. (Priced and sold individually).	\$	2,650.00
CBT 1000-WH	CBT 1000-WH	High-Output Two-Way Line Array Column with Highly Adjustable Vertical Coverage and Tapered Horizontal Waveguide. Same as CBT1000, in white. (Priced and sold individually).	\$	2,650.00
IVX-97665012	IVX-97665012	Dummy Enclosure. Intellivox 280 series. Made to Order Call for availability	\$	2,672.00
VRX932LA-1	VRX932LA-1	12" two-way line-array system with 1 x 2262H Differential Drive® LF; 3 x 2408J Annular Ring Diaphragm HF on Constant Curvature waveguide; dual angle pole socket and integral rigging hardware; passive or bi-amplified operation. Black DuraFlex™ finish.	\$	2,759.00

VRX932LA-1WH	VRX932LA-1WH	12" two-way line-array system with 1 x 2262H Differential Drive® LF; 3 x 2408J Annular Ring Diaphragm HF on Constant Curvature waveguide; dual angle pole socket and integral rigging hardware; passive or bi-amplified operation. White DuraFlex™ finish.	\$	2,759.00
CWT128	CWT128	Crossfired Waveguide Technology. Extremely wide coverage dual 8", dual 2408H-1 compression drivers in a compact 2-way passive loudspeaker system. 400W Watt pink noise power handling. 1600 Watt peak power handling. 126 dB maximum SPL, 8 ohms. Foam backed powder coated 16 gauge steel grille. Four M10 suspension points and OmniMount® provision on rear panel. Standard finish: Black DuraFlex™. Optional finishes: White (-WH), WRC and WRX. Net weight 18.6 kg (40.9 lbs). Priced as each.	\$	2,760.00
CWT128-WH	CWT128-WH	Crossfired Waveguide Technology. Extremely wide coverage dual 8", dual 2408H-1 compression drivers in a compact 2-way passive loudspeaker system. 400W Watt pink noise power handling. 1600 Watt peak power handling. 126 dB maximum SPL, 8 ohms. Foam backed powder coated 16 gauge steel grille. Four M10 suspension points and OmniMount® provision on rear panel. Standard finish: Black DuraFlex™. Optional finishes: White (-WH), WRC and WRX. Net weight 18.6 kg (40.9 lbs). Priced as each.	\$	2,760.00
PD5122	PD5122	High Output Low Frequency Loudspeaker with 12" Slot Loaded Woofers. Two 300mm (12 in.) VGC™ Vented Gap Cooled 2206H Low Frequency Drivers in a Slot Loaded, Vented Configuration. Same as LF Section in PD5322 Series. 41 Hz to 1 Hz Frequency Range. 375 x 673 x 706 mm (14.8 x 26.5 x 27.8 in.), 36.4 kg (80 lb). *NEW*	\$	2,822.00
PD5122-WH	PD5122-WH	High Output Low Frequency Loudspeaker with 12" Slot Loaded Woofers. Two 300mm (12 in.) VGC™ Vented Gap Cooled 2206H Low Frequency Drivers in a Slot Loaded, Vented Configuration. Same as LF Section in PD5322 Series. 41 Hz to 1 Hz Frequency Range. 375 x 673 x 706 mm (14.8 x 26.5 x 27.8 in.), 36.4 kg (80 lb). White finish. *NEW*	\$	2,822.00
ASB4128	ASB4128	Medium Power Dual 18" Subwoofer, 2 x 18" 2042H Drivers, Parallel/Discrete Switchable. Priced as each. Suspension Eyebolts Not Included.	\$	2,872.00
ASB4128-WH	ASB4128-WH	Medium Power Dual 18" Subwoofer, 2 x 18" 2042H Drivers, Parallel/Discrete Switchable. Priced as each. Suspension Eyebolts Not Included. White finish.	\$	2,872.00
AM7212/00	AM7212/00	High Power 12" 2-Way Full-Range Loudspeaker System with JBL Differential Drive® 75mm (3-in) dual voice coil and dual magnetic gap 2262H low frequency driver and 2432H high-frequency 38mm (1.5 in) exit, 75mm (3 in) voice-coil compression driver. 100° x 100° rotatable Progressive Transition™ waveguide, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Optional U-bracket model MTU-3.	\$	2,880.00
AM7212/00-WH	AM7212/00-WH	High Power 12" 2-Way Full-Range Loudspeaker System with JBL Differential Drive® 75mm (3-in) dual voice coil and dual magnetic gap 2262H low frequency driver and 2432H high-frequency 38mm (1.5 in) exit, 75mm (3 in) voice-coil compression driver. 100° x 100° rotatable Progressive Transition™ waveguide, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Optional U-bracket model MTU-3.	\$	2,880.00

AM7212/26	AM7212/26	High Power 12" 2-Way Full-Range Loudspeaker System with JBL Differential Drive® 75mm (3-in) dual voice coil and dual magnetic gap 2262H low frequency driver and 2432H high-frequency 38mm (1.5 in) exit, 75mm (3 in) voice-coil compression driver. 120° x 60° rotatable Progressive Transition™ waveguide, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Optional U-bracket model MTU-3.	\$	2,880.00
AM7212/26-WH	AM7212/26-WH	High Power 12" 2-Way Full-Range Loudspeaker System with JBL Differential Drive® 75mm (3-in) dual voice coil and dual magnetic gap 2262H low frequency driver and 2432H high-frequency 38mm (1.5 in) exit, 75mm (3 in) voice-coil compression driver. 120° x 60° rotatable Progressive Transition™ waveguide, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Optional U-bracket model MTU-3. White finish.	\$	2,880.00
AM7212/64	AM7212/64	High Power 12" 2-Way Full-Range Loudspeaker System with JBL Differential Drive® 75mm (3-in) dual voice coil and dual magnetic gap 2262H low frequency driver and 2432H high-frequency 38mm (1.5 in) exit, 75mm (3 in) voice-coil compression driver. 60° x 40° rotatable Progressive Transition™ waveguide, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Optional U-bracket model MTU-3.	\$	2,880.00
AM7212/64-WH	AM7212/64-WH	High Power 12" 2-Way Full-Range Loudspeaker System with JBL Differential Drive® 75mm (3-in) dual voice coil and dual magnetic gap 2262H low frequency driver and 2432H high-frequency 38mm (1.5 in) exit, 75mm (3 in) voice-coil compression driver. 60° x 40° rotatable Progressive Transition™ waveguide, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Optional U-bracket model MTU-3. White finish.	\$	2,880.00
AM7212/66	AM7212/66	High Power 12" 2-Way Full-Range Loudspeaker System with JBL Differential Drive® 75mm (3-in) dual voice coil and dual magnetic gap 2262H low frequency driver and 2432H high-frequency 38mm (1.5 in) exit, 75mm (3 in) voice-coil compression driver. 60° x 60° rotatable Progressive Transition™ waveguide, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Optional U-bracket model MTU-3.	\$	2,880.00
AM7212/66-WH	AM7212/66-WH	High Power 12" 2-Way Full-Range Loudspeaker System with JBL Differential Drive® 75mm (3-in) dual voice coil and dual magnetic gap 2262H low frequency driver and 2432H high-frequency 38mm (1.5 in) exit, 75mm (3 in) voice-coil compression driver. 60° x 60° rotatable Progressive Transition™ waveguide, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Optional U-bracket model MTU-3. White finish.	\$	2,880.00

AM7212/95	AM7212/95	High Power 12" 2-Way Full-Range Loudspeaker System with JBL Differential Drive® 75 mm (3-in) dual voice coil and dual magnetic gap 2262H low frequency driver and 2432H high-frequency 38mm (1.5 in) exit, 75mm (3 in) voice-coil compression driver. 90° x 50° rotatable Progressive Transition™ waveguide, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Optional U-bracket model MTU-3.	\$	2,880.00
AM7212/95-WH	AM7212/95-WH	High Power 12" 2-Way Full-Range Loudspeaker System with JBL Differential Drive® 75 mm (3-in) dual voice coil and dual magnetic gap 2262H low frequency driver and 2432H high-frequency 38mm (1.5 in) exit, 75mm (3 in) voice-coil compression driver. 90° x 50° rotatable Progressive Transition™ waveguide, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Optional U-bracket model MTU-3. White finish.	\$	2,880.00
ASB6125	ASB6125	Dual 15" High-Power Subwoofer System. 2 x 2265H-1 Differential Drive® woofer, 3" dual voice coil – dual gap, neodymium magnet. Multiply hardwood enclosure with DuraFlex™ finish and 14-gauge steel grille. Sixteen M10 suspension points. Available in Black and White. Priced as each.	\$	2,910.00
ASB6125-WH	ASB6125-WH	Dual 15" High-Power Subwoofer System. 2 x 2265H-1 Differential Drive® woofer, 3" dual voice coil – dual gap, neodymium magnet. Multiply hardwood enclosure with DuraFlex™ finish and 14-gauge steel grille. Sixteen M10 suspension points. White finish. Priced as each.	\$	2,910.00
AM7215/26	AM7215/26	High Power 15" 2-Way Full-Range Loudspeaker System with JBL Differential Drive® 75mm (3-in) dual voice coil and dual magnetic gap 2265H low frequency driver and 2432H high-frequency 38mm (1.5 in) exit, 75mm (3 in) voice-coil compression driver. 120° x 60° rotatable Progressive Transition™ waveguide, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Optional U-bracket model MTU-1.	\$	3,024.00
AM7215/26-WH	AM7215/26-WH	High Power 15" 2-Way Full-Range Loudspeaker System with JBL Differential Drive® 75mm (3-in) dual voice coil and dual magnetic gap 2265H low frequency driver and 2432H high-frequency 38mm (1.5 in) exit, 75mm (3 in) voice-coil compression driver. 120° x 60° rotatable Progressive Transition™ waveguide, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Optional U-bracket model MTU-1. White finish.	\$	3,024.00
AM7215/64	AM7215/64	High Power 15" 2-Way Full-Range Loudspeaker System with JBL Differential Drive® 75mm (3-in) dual voice coil and dual magnetic gap 2265H low frequency driver and 2432H high-frequency 38mm (1.5 in) exit, 75mm (3 in) voice-coil compression driver. 60° x 40° rotatable Progressive Transition™ waveguide, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Optional U-bracket model MTU-1	\$	3,024.00

		High Power 15" 2-Way Full-Range Loudspeaker System with JBL Differential Drive® 75mm (3-in) dual voice coil and dual magnetic gap 2265H low frequency driver and 2432H high-frequency 38mm (1.5 in) exit, 75mm (3 in) voice-coil compression driver. 60° x 40° rotatable Progressive Transition™ waveguide, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Optional U-bracket model MTU-1. White finish.		
AM7215/64-WH	AM7215/64-WH		\$	3,024.00
		High Power 15" 2-Way Full-Range Loudspeaker System with JBL Differential Drive® 75mm (3-in) dual voice coil and dual magnetic gap 2265H low frequency driver and 2432H high-frequency 38mm (1.5 in) exit, 75mm (3 in) voice-coil compression driver. 60° x 60° rotatable Progressive Transition™ waveguide, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Optional U-bracket model MTU-1.		
AM7215/66	AM7215/66		\$	3,024.00
		High Power 15" 2-Way Full-Range Loudspeaker System with JBL Differential Drive® 75mm (3-in) dual voice coil and dual magnetic gap 2265H low frequency driver and 2432H high-frequency 38mm (1.5 in) exit, 75mm (3 in) voice-coil compression driver. 60° x 60° rotatable Progressive Transition™ waveguide, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Optional U-bracket model MTU-1. White finish.		
AM7215/66-WH	AM7215/66-WH		\$	3,024.00
		High Power 15" 2-Way Full-Range Loudspeaker System with JBL Differential Drive® 75mm (3-in) dual voice coil and dual magnetic gap 2265H low frequency driver and 2432H high-frequency 38mm (1.5 in) exit, 75mm (3 in) voice-coil compression driver. 90° x 50° rotatable Progressive Transition™ waveguide, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Optional U-bracket model MTU-1.		
AM7215/95	AM7215/95		\$	3,024.00
		High Power 15" 2-Way Full-Range Loudspeaker System with JBL Differential Drive® 75mm (3-in) dual voice coil and dual magnetic gap 2265H low frequency driver and 2432H high-frequency 38mm (1.5 in) exit, 75mm (3 in) voice-coil compression driver. 90° x 50° rotatable Progressive Transition™ waveguide, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Optional U-bracket model MTU-1. White finish.		
AM7215/95-WH	AM7215/95-WH		\$	3,024.00
		High Power Mid-High Frequency Loudspeaker with JBL CMCD-82H mid driver, and 2432H High Frequency 38mm (1.5 in) exit, 75mm (3-in) voice coil compression driver. 60° x 40° Coverage, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Fits Optional Planar Array Frame Kits PAF-2K and PAF-3K. See AE Bracket Handbook for Details.		
AM7200/64	AM7200/64		\$	3,176.00
		High Power Mid-High Frequency Loudspeaker with JBL CMCD-82H mid driver, and 2432H High Frequency 38mm (1.5 in) exit, 75mm (3-in) voice coil compression driver. 90° x 50° Coverage, Bi-Amp/Passive Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Fits Optional Planar Array Frame Kits PAF-2K and PAF-3K. See AE Bracket Handbook for Details.		
AM7200/95	AM7200/95		\$	3,176.00

SUB18	SUB18	SUB 18 Studio subwoofer. (Speaker Only. Requires External Power Amplifier) Designed for applications in which very high continuous output and extended low frequency performance are required. Delivers unprecedented performance for demanding dance music production, while providing exceptional accuracy required in cinema post production applications. As an add-on to JBL's M2 Master Reference Monitor system, the SUB18 allows three times greater output from the system.	\$	3,250.00
VRX932LAP	VRX932LAP	Powered 12" two-way line-array system with 1 x 2262H Differential Drive® LF, 3 x 2408J HF on Constant Curvature waveguide; Crown DPC-2 amplifier module with system DSP; dual angle pole socket and integral rigging hardware; black DuraFlex™ finish.	\$	3,429.00
ASB7118	ASB7118	Ultra High-Power 18" Subwoofer System. . 2269H Differential Drive® Vented Gap™ woofer, 4" dual voice coil – dual gap, neodymium magnet. Multiply hardwood enclosure with DuraFlex™ finish and 14-gauge steel grille. Sixteen M10 suspension points. Available in Black and White. Priced as each.	\$	3,572.00
ASB7118-WH	ASB7118-WH	Ultra High-Power 18" Subwoofer System. . 2269H Differential Drive® Vented Gap™ woofer, 4" dual voice coil – dual gap, neodymium magnet. Multiply hardwood enclosure with DuraFlex™ finish and 14-gauge steel grille. Sixteen M10 suspension points. White finish. Priced as each.	\$	3,572.00
PD544	PD544	15" Horn-Loaded 2-way full-range system, 40? x 40? coverage pattern with 2432H 38mm (1.5 in) exit, 75mm (3 in) voice coil and 2031H 15" low-frequency driver with 75mm (3 in) voice coil, 8 ohm nominal system impedance.	\$	3,600.00
PD544 - WH	PD544 - WH	15" Horn-Loaded 2-way full-range system, 40? x 40? coverage pattern with 2432H 38mm (1.5 in) exit, 75mm (3 in) voice coil and 2031H 15" low-frequency driver with 75mm (3 in) voice coil, 8 ohm nominal system impedance. *NEW*	\$	3,600.00
PD564	PD564	15" Horn-Loaded 2-way full-range system, rotatable 60? x 40? coverage pattern with 2432H 38mm (1.5 in) exit, 75mm (3 in) voice coil and 2031H 15" low-frequency driver with 75mm (3 in) voice coil, 8 ohm nominal system impedance.	\$	3,600.00
PD564 - WH	PD564 - WH	15" Horn-Loaded 2-way full-range system, rotatable 60? x 40? coverage pattern with 2432H 38mm (1.5 in) exit, 75mm (3 in) voice coil and 2031H 15" low-frequency driver with 75mm (3 in) voice coil, 8 ohm nominal system impedance. *NEW*	\$	3,600.00
PD566 - WH	PD566 - WH	15" Horn-Loaded 2-way full-range system, 60? x 60? coverage pattern with 2432H 38mm (1.5 in) exit, 75mm (3 in) voice coil and 2031H 15" low-frequency driver with 75mm (3 in) voice coil, 8 ohm nominal system impedance. *NEW*	\$	3,600.00

15" Horn-Loaded 2-way full-range system, rotatable
 90° x 50° coverage pattern with 2432H 38mm (1.5 in) exit,
 75mm (3 in) voice coil and 2031H 15" low-frequency driver with
 75mm (3 in) voice coil, 8 ohm nominal system impedance.

PD595	PD595		\$	3,600.00
		15" Horn-Loaded 2-way full-range system, rotatable 90° x 50° coverage pattern with 2432H 38mm (1.5 in) exit, 75mm (3 in) voice coil and 2031H 15" low-frequency driver with 75mm (3 in) voice coil, 8 ohm nominal system impedance.		
PD595 -WH	PD595 -WH		\$	3,600.00
		High Output Two-Way MID/HIGH Frequency Loudspeaker with 8" MF and 60° x 40° Coverage Pattern. 200 mm (8 in.) CMCD- 82H™ Cone Midrange Compression Driver and Large Format 2431H Neodymium HF Driver. 200 Hz to 17 kHz Frequency Range. 991 x 673 x 706 mm. (39 x 26.5 x 27.8 in), 58.8 kg (130 lbs).		
PD6200/64	PD6200/64		\$	3,600.00
		High Output Two-Way MID/HIGH Frequency Loudspeaker with 8" MF and 60° x 40° Coverage Pattern. 200 mm (8 in.) CMCD- 82H™ Cone Midrange Compression Driver and Large Format 2431H Neodymium HF Driver. 200 Hz to 17 kHz Frequency Range. 991 x 673 x 706 mm. (39 x 26.5 x 27.8 in), 58.8 kg (130 lbs).		
PD6200/64-WH	PD6200/64-WH	White finish.	\$	3,600.00
		High Output Two-Way MID/HIGH Frequency Loudspeaker with 8" MF and 60° x 60° Coverage Pattern. 200 mm (8 in.) CMCD- 82H™ Cone Midrange Compression Driver and Large Format 2431H Neodymium HF Driver. 200 Hz to 17 kHz Frequency Range. 991 x 673 x 706 mm. (39 x 26.5 x 27.8 in), 58.8 kg (130 lbs).		
PD6200/66	PD6200/66		\$	3,600.00
		High Output Two-Way MID/HIGH Frequency Loudspeaker with 8" MF and 60° x 60° Coverage Pattern. 200 mm (8 in.) CMCD- 82H™ Cone Midrange Compression Driver and Large Format 2431H Neodymium HF Driver. 200 Hz to 17 kHz Frequency Range. 991 x 673 x 706 mm. (39 x 26.5 x 27.8 in), 58.8 kg (130 lbs).		
PD6200/66-WH	PD6200/66-WH	White finish.	\$	3,600.00
		High Output Two-Way MID/HIGH Frequency Loudspeaker with 8" MF and 90° x 50° Coverage Pattern. 200 mm (8 in.) CMCD- 82H™ Cone Midrange Compression Driver and Large Format 2431H Neodymium HF Driver. 200 Hz to 17 kHz Frequency Range. 991 x 673 x 706 mm. (39 x 26.5 x 27.8 in), 58.8 kg (130 lbs).		
PD6200/95	PD6200/95		\$	3,600.00
		High Output Two-Way MID/HIGH Frequency Loudspeaker with 8" MF and 90° x 50° Coverage Pattern. 200 mm (8 in.) CMCD- 82H™ Cone Midrange Compression Driver and Large Format 2431H Neodymium HF Driver. 200 Hz to 17 kHz Frequency Range. 991 x 673 x 706 mm. (39 x 26.5 x 27.8 in), 58.8 kg (130 lbs).		
PD6200/95-WH	PD6200/95-WH	White finish.	\$	3,600.00
		Intonato 24 Monitor Management Tuning System. Ideal for use with JBL M2, 7 Series studio monitors. Provides automated calibration and control of stereo, surround and immersive audio monitoring systems. 24 speaker outputs, 24 analog and digital inputs. Flexible routing and monitoring configurations, store and recall of custom user profiles. 2-U rack mount ready. Calibration microphone included. Comprehensive control via supplied Macintosh Windows, and tablet software. Optional Intonato Desk Top Controller.		
INTONATO24FX	INTONATO24FX		\$	3,750.00

ASB6128	ASB6128	High Power Dual 18" Subwoofer. 2 x 18" 2242H VGC™ Driver, Parallel/Discrete Switchable. Suspension Eyebolts Not Included. Arrays with AM6340 and AM4340 Loudspeakers Using PAF-2K Planar Array Frame Kit. Priced as each.	\$	3,762.00
ASB6128-WH	ASB6128-WH	High Power Dual 18" Subwoofer. 2 x 18" 2242H VGC™ Driver, Parallel/Discrete Switchable. Suspension Eyebolts Not Included. Arrays with AM6340 and AM4340 Loudspeakers Using PAF-2K Planar Array Frame Kit. White finish. Priced as each.	\$	3,762.00
ASH6118	ASH6118	Horn Loaded Subwoofer, Maximum Low Frequency Output & Sensitivity. 1 x 18" 2242H SVG™ Driver. Designed to be Used In Multiples (2 Minimum, 4 Optimum) with Proximity Placement Or With Proper Boundary Surface Loading. Not Suspendable. Special Order, Typical 4 Week Lead Time. Priced as each.	\$	3,932.00
AW266	AW266	High Output 12" 2-way Full-Range 60 x 60 Loudspeaker-GRAY. Priced as each.	\$	3,982.00
AW266-BK	AW266-BK	High Output 12" 2-way Full-Range 60 x 60 Loudspeaker-BLACK. Priced as each.	\$	3,982.00
AW266-LS	AW266-LS	12" 2-Way All Weather Loudspeaker with EN54-24 Certification. Priced as each.	\$	3,982.00
AW266-LS-BK	AW266-LS-BK	12" 2-Way All Weather Loudspeaker with EN54-24 Certification, black. Priced as each.	\$	3,982.00
AW295	AW295	High Output 12" 2-way Full-Range 90 x 50 Loudspeaker-GRAY. Priced as each.	\$	3,982.00
AW295-BK	AW295-BK	High Output 12" 2-way Full-Range 90 x 50 Loudspeaker-BLACK. Priced as each.	\$	3,982.00
AW295-LS	AW295-LS	12" 2-Way All Weather Loudspeaker with EN54-24 Certification. Priced as each.	\$	3,982.00
PD6212/64	PD6212/64	High Sensitivity Two-Way FULL-RANGE Loudspeaker with Horn Loaded 12" LF and 60° x 40° Coverage Pattern. 300 mm (12 in.) M222- 8A Horn-loaded LF and Large Format 2451H-1 Neodymium HF Driver. 80 Hz to 18 kHz Frequency Range. 991 x 673 x 706 mm. (39 x 26.5 x 27.8 in), 69 kg (152 lbs).	\$	4,080.00
PD6212/64-WH	PD6212/64-WH	High Sensitivity Two-Way FULL-RANGE Loudspeaker with Horn Loaded 12" LF and 60° x 40° Coverage Pattern. 300 mm (12 in.) M222- 8A Horn-loaded LF and Large Format 2451H-1 Neodymium HF Driver. 80 Hz to 18 kHz Frequency Range. 991 x 673 x 706 mm. (39 x 26.5 x 27.8 in), 69 kg (152 lbs).	\$	4,080.00
PD6212/66	PD6212/66	High Sensitivity Two-Way FULL-RANGE Loudspeaker with Horn Loaded 12" LF and 60° x 60° Coverage Pattern. 300 mm (12 in.) M222- 8A Horn-loaded LF and Large Format 2451H-1 Neodymium HF Driver. 80 Hz to 18 kHz Frequency Range. 991 x 673 x 706 mm. (39 x 26.5 x 27.8 in), 69 kg (152 lbs).	\$	4,080.00
PD6212/66-WH	PD6212/66-WH	High Sensitivity Two-Way FULL-RANGE Loudspeaker with Horn Loaded 12" LF and 60° x 60° Coverage Pattern. 300 mm (12 in.) M222- 8A Horn-loaded LF and Large Format 2451H-1 Neodymium HF Driver. 80 Hz to 18 kHz Frequency Range. 991 x 673 x 706 mm. (39 x 26.5 x 27.8 in), 69 kg (152 lbs). White finish.	\$	4,080.00
PD6212/95	PD6212/95	High Sensitivity Two-Way FULL-RANGE Loudspeaker with Horn Loaded 12" LF and 90° x 50° Coverage Pattern. 300 mm (12 in.) M222- 8A Horn-loaded LF and Large Format 2451H-1 Neodymium HF Driver. 80 Hz to 18 kHz Frequency Range. 991 x 673 x 706 mm. (39 x 26.5 x 27.8 in), 69 kg (152 lbs).	\$	4,080.00

		High Sensitivity Two-Way FULL-RANGE Loudspeaker with Horn Loaded 12" LF and 90° x 50° Coverage Pattern. 300 mm (12 in.) M222- 8A Horn-loaded LF and Large Format 2451H-1 Neodymium HF Driver. 80 Hz to 18 kHz Frequency Range. 991 x 673 x 706 mm. (39 x 26.5 x 27.8 in), 69 kg (152 lbs). White finish	\$	4,080.00
PD6212/95-WH	PD6212/95-WH			
		Extended Response, High Power Dual 18" Subwoofer. 2 x 18" 2258H NDD™ Neodymium Dual Drive Transducers in V-Loaded Configuration, Deep Cabinet, Driver Magnets Outward For Maximum Cooling, , Parallel/Discrete Switchable. Suspension Eyebolts Not Included. Arrays with AM6315 and AM4315 Loudspeakers Using PAF-2K Planar Array Frame Kit. Priced as each.	\$	4,114.00
ASB6128V	ASB6128V			
		High Power 3-Way Full-Range Loudspeaker System with JBL Differential Drive® 75mm (3-in) dual voice coil and dual magnetic gap 2265H low frequency driver, CMCD-82H mid driver, and 2432H high-frequency 38mm (1.5 in) exit, 75mm (3 in) voice-coil compression driver. 60° x 40° Coverage, Bi-Amp/Tri-Amp Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Fits Optional Planar Array Frame Kits PAF-2K and PAF-3K. See AE Bracket Handbook for Details.	\$	4,296.00
AM7315/64	AM7315/64			
		High Power 3-Way Full-Range Loudspeaker System with JBL Differential Drive® 75mm (3-in) dual voice coil and dual magnetic gap 2265H low frequency driver, CMCD-82H mid driver, and 2432H high-frequency 38mm (1.5 in) exit, 75mm (3 in) voice-coil compression driver. 60° x 40° Coverage, Bi-Amp/Tri-Amp Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Fits Optional Planar Array Frame Kits PAF-2K and PAF-3K. See AE Bracket Handbook for Details.	\$	4,296.00
AM7315/64-WH	AM7315/64-WH			
		High Power 3-Way Full-Range Loudspeaker System with JBL Differential Drive® 75mm (3-in) dual voice coil and dual magnetic gap 2265H low frequency driver, CMCD-82H mid driver, and 2432H high-frequency 38mm (1.5 in) exit, 75mm (3 in) voice-coil compression driver. 90° x 50° Coverage, Bi-Amp/Tri-Amp Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Fits Optional Planar Array Frame Kits PAF-2K and PAF-3K. See AE Bracket Handbook for Details.	\$	4,296.00
AM7315/95	AM7315/95			
		High Power 3-Way Full-Range Loudspeaker System with JBL Differential Drive® 75mm (3-in) dual voice coil and dual magnetic gap 2265H low frequency driver, CMCD-82H mid driver, and 2432H high-frequency 38mm (1.5 in) exit, 75mm (3 in) voice-coil compression driver. 90° x 50° Coverage, Bi-Amp/Tri-Amp Switchable. Available in Black or White (-WH). Priced as each. Suspension eyebolts not included. Fits Optional Planar Array Frame Kits PAF-2K and PAF-3K. See AE Bracket Handbook for Details.	\$	4,296.00
AM7315/95-WH	AM7315/95-WH			
		High Output 15" 2-way Full-Range 120 x 60 Loudspeaker-GRAY. Priced as each.	\$	4,310.00
AW526	AW526			
		High Output 15" 2-way Full-Range 120 x 60 Loudspeaker-BLACK. Priced as each.	\$	4,310.00
AW526-BK	AW526-BK			
		15" 2-Way All Weather Loudspeaker with EN54-24 Certification. Priced as each.	\$	4,310.00
AW526-LS	AW526-LS			
		15" 2-Way All Weather Loudspeaker with EN54-24 Certification, black. Priced as each.	\$	4,310.00
AW526-LS-BK	AW526-LS-BK			
		High Output 15" 2-way Full-Range 60 x 60 Loudspeaker-GRAY. Priced as each.	\$	4,310.00
AW566	AW566			
		High Output 15" 2-way Full-Range 60 x 60 Loudspeaker-BLACK. Priced as each.	\$	4,310.00
AW566-BK	AW566-BK			

AW566-LS	AW566-LS	15" 2-Way All Weather Loudspeaker with EN54-24 Certification. Priced as each.	\$	4,310.00
AW566-LS-BK	AW566-LS-BK	15" 2-Way All Weather Loudspeaker with EN54-24 Certification, black. Priced as each.	\$	4,310.00
AW595	AW595	High Output 15" 2-way Full-Range 90 x 50 Loudspeaker-GRAY. Priced as each.	\$	4,310.00
AW595-BK	AW595-BK	High Output 15" 2-way Full-Range 90 x 50 Loudspeaker-BLACK. Priced as each.	\$	4,310.00
AW595-LS	AW595-LS	15" 2-Way All Weather Loudspeaker with EN54-24 Certification. Priced as each.	\$	4,310.00
AW595-LS-BK	AW595-LS-BK	15" 2-Way All Weather Loudspeaker with EN54-24 Certification, black. Priced as each.	\$	4,310.00
VT4886	VT4886	Subcompact 2 x 6.5" Passive 3-Way High Directivity Line Array Element Loudspeaker with 2x JBL Differential Drive® dual voice coil and dual magnetic gap 2166H 165mm (6.5") low frequency drivers, 4x 2103G 2.5" midrange drivers and 2x 2414H high-frequency 25.4mm (1 in) voice-coil compression drivers. Integrated MF/HF Waveguide with RBI (Radiation Boundary Integrator® and Thermomaster® Technology, Three-way passive network, Patented Integrated Suspension Hardware. Perforated Steel Grilles with Foam Backing, Two Handles. NL8 and NL4 Connectors. Combine to Form Articulated Arrays.	\$	4,374.24
VT4883	VT4883	Subcompact 2 x 12" Cardioid-Arrayable Subwoofer Loudspeaker with 2x JBL Differential Drive® dual voice coil and dual magnetic gap 2263H-1 12" long-excursion low frequency drivers. Vented-Bandpass Enclosure Topology with Rigid Internal Bracing. Pole Mount. Designed for Reverse-Arrayable Orientation to create Gradient Cardioid Subwoofer Arrays. Patented Integrated Suspension Hardware. Perforated Steel Grilles with Foam Backing, Four Handles. NL8 and NL4 Connectors with Front Auxiliary Connector. Combine in Arrays with VT4886.	\$	4,536.48
IVX-97745012	IVX-97745012	Dummy Enclosure. Intellivox 430 series. Made to Order Call for availability	\$	4,626.00
PD6322/64-H	PD6322/64-H	High Output Three-Way FULL-RANGE Loudspeaker with 12" LF, 8" MF and 60° x 40° Coverage Pattern. Two 300 mm (12 in.) VGC™ Vented Gap Cooled 2206H Woofers in a Slot Loaded LF, 200 mm (8 in) CMCD™ Cone Midrange Compression Driver and Large Format 2431H Neodymium HF Driver. 41 Hz to 17 kHz Frequency Range. 991 x 673 x 706 mm. (39 x 26.5 x 27.8 in), 77 kg (170 lbs).	\$	4,800.00
PD6322/64-WH	PD6322/64-WH	High Output Three-Way FULL-RANGE Loudspeaker with 12" LF, 8" MF and 60° x 40° Coverage Pattern. Two 300 mm (12 in.) VGC™ Vented Gap Cooled 2206H Woofers in a Slot Loaded LF, 200 mm (8 in) CMCD™ Cone Midrange Compression Driver and Large Format 2431H Neodymium HF Driver. 41 Hz to 17 kHz Frequency Range. 991 x 673 x 706 mm. (39 x 26.5 x 27.8 in), 77 kg (170 lbs). White finish.	\$	4,800.00
PD6322/66	PD6322/66	High Output Three-Way FULL-RANGE Loudspeaker with 12" LF, 8" MF and 60° x 60° Coverage Pattern. Two 300 mm (12 in.) VGC™ Vented Gap Cooled 2206H Woofers in a Slot Loaded LF, 200 mm (8 in) CMCD™ Cone Midrange Compression Driver and Large Format 2431H Neodymium HF Driver. 41 Hz to 17 kHz Frequency Range. 991 x 673 x 706 mm. (39 x 26.5 x 27.8 in), 77 kg (170 lbs).	\$	4,800.00

PD6322/66-WH	PD6322/66-WH	High Output Three-Way FULL-RANGE Loudspeaker with 12" LF, 8" MF and 60° x 60° Coverage Pattern. Two 300 mm (12 in.) VGC™ Vented Gap Cooled 2206H Woofers in a Slot Loaded LF, 200 mm (8 in) CMCD™ Cone Midrange Compression Driver and Large Format 2431H Neodymium HF Driver. 41 Hz to 17 kHz Frequency Range. 991 x 673 x 706 mm. (39 x 26.5 x 27.8 in), 77 kg (170 lbs). White finish.	\$	4,800.00
PD6322/95	PD6322/95	High Output Three-Way FULL-RANGE Loudspeaker with 12" LF, 8" MF and 90° x 50° Coverage Pattern. Two 300 mm (12 in.) VGC™ Vented Gap Cooled 2206H Woofers in a Slot Loaded LF, 200 mm (8 in) CMCD™ Cone Midrange Compression Driver and Large Format 2431H Neodymium HF Driver. 41 Hz to 17 kHz Frequency Range. 991 x 673 x 706 mm. (39 x 26.5 x 27.8 in), 77 kg (170 lbs).	\$	4,800.00
PD6322/95-WH	PD6322/95-WH	High Output Three-Way FULL-RANGE Loudspeaker with 12" LF, 8" MF and 90° x 50° Coverage Pattern. Two 300 mm (12 in.) VGC™ Vented Gap Cooled 2206H Woofers in a Slot Loaded LF, 200 mm (8 in) CMCD™ Cone Midrange Compression Driver and Large Format 2431H Neodymium HF Driver. 41 Hz to 17 kHz Frequency Range. 991 x 673 x 706 mm. (39 x 26.5 x 27.8 in), 77 kg (170 lbs). White finish.	\$	4,800.00
VLA-C125S-GR	VLA-C125S-GR	Same as VLA-C125S-BK, but in Gray.	\$	4,800.00
VLA-C125S-BK	VLA-C125S-BK	Subwoofer for VLA Compact line array system. Dual 15" Differential Drive® transducers. Comes standard with IP55 weather protection, with fiberglass enclosure and stainless steel components. Black.	\$	4,800.00
PD6200/43	PD6200/43	High Output Two-Way MID/HIGH Frequency Loudspeaker with 8" MF and 40° x 30° Coverage Pattern. 200 mm (8 in.) CMCD™ Cone Midrange Compression Driver and Large Format 2431H Neodymium HF Driver. 200 Hz to 17 kHz Frequency Range. 991 x 673 x 706 mm. (39 x 26.5 x 27.8 in), 58.8 kg (130 lbs).	\$	5,160.00
PD6200/43-WH	PD6200/43-WH	High Output Two-Way MID/HIGH Frequency Loudspeaker with 8" MF and 40° x 30° Coverage Pattern. 200 mm (8 in.) CMCD™ Cone Midrange Compression Driver and Large Format 2431H Neodymium HF Driver. 200 Hz to 17 kHz Frequency Range. 991 x 673 x 706 mm. (39 x 26.5 x 27.8 in), 58.8 kg (130 lbs). White finish.	\$	5,160.00
IVX-587000	IVX-587000	Intellivox-DS115, Amp@Bottom. Made to Order Call for availability	\$	5,324.00
IVX-587001	IVX-587001	Intellivox-DS115, Amp@Top. Made to Order Call for availability	\$	5,324.00
PD6212/43	PD6212/43	High Sensitivity Two-Way FULL-RANGE Loudspeaker with Horn Loaded 12" LF and 40° x 30° Coverage Pattern. 300 mm (12 in.) M222- 8A Horn-loaded LF and Large Format 2451H-1 Neodymium HF Driver. 80 Hz to 18 kHz Frequency Range. 991 x 673 x 897 mm. (39 x 26.5 x 35.3 in), 79.5 kg (175 lbs).	\$	5,640.00
PD6212/43-WH	PD6212/43-WH	High Sensitivity Two-Way FULL-RANGE Loudspeaker with Horn Loaded 12" LF and 40° x 30° Coverage Pattern. 300 mm (12 in.) M222- 8A Horn-loaded LF and Large Format 2451H-1 Neodymium HF Driver. 80 Hz to 18 kHz Frequency Range. 991 x 673 x 897 mm. (39 x 26.5 x 35.3 in), 79.5 kg (175 lbs). White finish.	\$	5,640.00
VLA-C2100-GR	VLA-C2100-GR	Same as VLA-C2100-BK, but in Gray.	\$	5,800.00
VLA-C2100-BK	VLA-C2100-BK	Two-way horn-loaded line array loudspeaker system. 100° horizontal horn coverage pattern. 2x10"LF, 3x0.8" Exit HF. Comes standard with IP55 weather protection, with fiberglass enclosure and stainless steel components. Bi-amp or passive (field switchable). Black.	\$	5,800.00
VLA-C265-GR	VLA-C265-GR	Same as VLA-C265-BK, but in Gray.	\$	5,800.00

VLA-C265-BK	VLA-C265-BK	Two-way horn-loaded line array loudspeaker system. 65° horizontal horn coverage pattern. 2x10" LF, 3x0.8" Exit HF. Comes standard with IP55 weather protection, with fiberglass enclosure and stainless steel components. Bi-amp or passive (field switchable). Black.	\$	5,800.00
M2	M2	M2 Master Reference Monitor: A Free-Standing, 2-Way System that can be placed in any environment to provide an exceptionally accurate monitoring experience. Leveraging a new generation of JBL high-output, ultra-low distortion transducers, the M2 provides in-room frequency response of 20 Hz to 40 kHz, and an extraordinary 123 dB maximum SPL to meet the demanding music, cinema and broadcast production requirements for impactful dynamic range.	\$	6,000.00
ASB7128	ASB7128	Dual 18" Ultra High-Power Subwoofer System. 2 x 2269H Differential Drive® Vented Gap™ woofer, 4" dual voice coil – dual gap, neodymium magnet. Multiply hardwood enclosure with DuraFlex™ finish and 14-gauge steel grille. Sixteen M10 suspension points. Available in Black and White. Priced as each.	\$	6,268.00
ASB7128-WH	ASB7128-WH	Dual 18" Ultra High-Power Subwoofer System. 2 x 2269H Differential Drive® Vented Gap™ woofer, 4" dual voice coil – dual gap, neodymium magnet. Multiply hardwood enclosure with DuraFlex™ finish and 14-gauge steel grille. Sixteen M10 suspension points. White finish. Priced as each.	\$	6,268.00
PD6322/43	PD6322/43	High Output Three-Way FULL-RANGE Loudspeaker with 12" LF, 8" MF and 40° x 30° Coverage Pattern. Two 300 mm Loaded LF Configuration, 200 mm (8 in) CMCD™ Cone MidRange Compression Driver and Large Format 2431H Neodymium HF Driver. 40 Hz to 17 kHz Frequency Range. 991 x 673 x 897 mm. (39 x 26.5 x 35.3 in), 87.3 kg (192 lbs).	\$	6,480.00
PD6322/43-WH	PD6322/43-WH	High Output Three-Way FULL-RANGE Loudspeaker with 12" LF, 8" MF and 40° x 30° Coverage Pattern. Two 300 mm Loaded LF Configuration, 200 mm (8 in) CMCD™ Cone MidRange Compression Driver and Large Format 2431H Neodymium HF Driver. 40 Hz to 17 kHz Frequency Range. 991 x 673 x 897 mm. (39 x 26.5 x 35.3 in), 87.3 kg (192 lbs). White finish.	\$	6,480.00
IVX-587020	IVX-587020	Intellivox-DS180, Amp@Bottom. Made to Order Call for availability	\$	7,805.00
IVX-587021	IVX-587021	Intellivox-DS180, Amp@Top. Made to Order Call for availability	\$	7,805.00
IVX-587040	IVX-587040	Intellivox-DSX180, Amp@Bottom. Made to Order Call for availability	\$	7,805.00
IVX-587041	IVX-587041	Intellivox-DSX180, Amp@Top. Made to Order Call for availability	\$	7,805.00
IVX-587060	IVX-587060	Intellivox-DS280, Amp@Bottom. Made to Order Call for availability	\$	10,688.00
IVX-587480	IVX-587480	Intellivox-DSX280HD, Amp@Bottom. Made to Order Call for availability	\$	10,688.00
IVX-587481	IVX-587481	Intellivox-DSX280HD, Amp@Top. Made to Order Call for availability	\$	10,688.00

		Precision Directivity™ Mid/High Frequency Coaxial with 40 x 30 Dispersion. Dual large format 2430H HF drivers with IFS™ Interference Free Summation, dual 2250J very high output 8" MF Drivers, well controlled dispersion to below 400 Hz, ten M10 integrated suspension points. 150 Hz to 16 kHz frequency range. 700 W MF, 150 W HF continuous power capability. Max SPL capability of 139 dB continuous, 145 peak. Compact 991 H x 991 W x 1146 D mm (39 x 39 x 45.1 in), 111.4 kg (245 lb).		
PD764	PD764		\$	11,340.00
		Precision Directivity™ Mid/High Frequency Coaxial with 40 x 30 Dispersion. Dual large format 2430H HF drivers with IFS™ Interference Free Summation, dual 2250J very high output 8" MF Drivers, well controlled dispersion to below 400 Hz, ten M10 integrated suspension points. 150 Hz to 16 kHz frequency range. 700 W MF, 150 W HF continuous power capability. Max SPL capability of 139 dB continuous, 145 peak. Compact 991 H x 991 W x 1146 D mm (39 x 39 x 45.1 in), 111.4 kg (245 lb). With Weather Protection Treatment. Refer to WEATHER RESISTANT Configurations for AE, PD & VLA Series document for details regarding WRC/WRX models. Standard color is GRAY. Available in Black (-BK) & White (-WH).8-10 weeks ship time for orders of 1-10, larger needs to be reviewed		
PD764-WH	PD764-WH		\$	11,340.00
IVX-587870	IVX-587870	Intellivox-HP-DS170, High Power. Made to Order Call for availability	\$	11,792.00
		Precision Directivity™ Mid/High Frequency Coaxial with 40 x 30 Dispersion. Dual large format 2430H HF drivers with IFS™ Interference Free Summation, dual 2250J very high output 8" MF Drivers, well controlled dispersion to below 400 Hz, ten M10 integrated suspension points. 150 Hz to 16 kHz frequency range. 700 W MF, 150 W HF continuous power capability. Max SPL capability of 139 dB continuous, 145 peak. Compact 991 H x 991 W x 1146 D mm (39 x 39 x 45.1 in), 111.4 kg (245 lb).		
PD743	PD743		\$	12,448.00
		Precision Directivity™ Mid/High Frequency Coaxial with 40 x 30 Dispersion. Dual large format 2430H HF drivers with IFS™ Interference Free Summation, dual 2250J very high output 8" MF Drivers, well controlled dispersion to below 400 Hz, ten M10 integrated suspension points. 150 Hz to 16 kHz frequency range. 700 W MF, 150 W HF continuous power capability. Max SPL capability of 139 dB continuous, 145 peak. Compact 991 H x 991 W x 1146 D mm (39 x 39 x 45.1 in), 111.4 kg (245 lb). With Weather Protection Treatment. Refer to WEATHER RESISTANT Configurations for AE, PD & VLA Series document for details regarding WRC/WRX models. Standard color is GRAY. Available in Black (-BK) & White (-WH).8-10 weeks ship time for orders of 1-10, larger needs to be reviewed		
PD743-WH	PD743-WH		\$	12,448.00
IVX-587300	IVX-587300	Intellivox-DS380, Amp@Bottom. Made to Order Call for availability	\$	15,125.00
IVX-587301	IVX-587301	Intellivox-DS380, Amp@Top. Made to Order Call for availability	\$	15,125.00
IVX-587350	IVX-587350	Intellivox-DSX380, Amp@Bottom. Made to Order Call for availability	\$	15,125.00
IVX-587351	IVX-587351	Intellivox-DSX380, Amp@Top. Made to Order Call for availability	\$	15,125.00
IVX-587120	IVX-587120	Intellivox-DS430, Amp@Bottom. Made to Order Call for availability	\$	18,503.00
IVX-587121	IVX-587121	Intellivox-DS430, Amp@Top. Made to Order Call for availability	\$	18,503.00

IVX-587140	IVX-587140	Intellivox-DSX430, Amp@Bottom. Made to Order Call for availability	\$	18,503.00
IVX-587141	IVX-587141	Intellivox-DSX430, Amp@Top. Made to Order Call for availability	\$	18,503.00
IVX-587160	IVX-587160	Intellivox-DS500, Amp@Bottom. Made to Order Call for availability	\$	21,074.00
IVX-587161	IVX-587161	Intellivox-DS500, Amp@Top. Made to Order Call for availability	\$	21,074.00
IVX-587180	IVX-587180	Intellivox-DSX500, Amp@Bottom. Made to Order Call for availability	\$	21,074.00
IVX-587181	IVX-587181	Intellivox-DSX500, Amp@Top. Made to Order Call for availability	\$	21,074.00
IVX-587890	IVX-587890	Intellivox-HP-DS370, High Power. Made to Order Call for availability	\$	25,666.00
JBLCSM21V	CSM-21	2 x 1 Stereo/Mono Public Address Mixer	\$	698.00
JBLCSM32V	CSM-32	3 x 2 Stereo/Mono Public Address Mixer	\$	838.00
JBLCSPM4	CSPM-4	CSM 4-Zone Paging Station	\$	174.00
JBLCSR2SVBLKV	CSR-2SV-BLK	Wall Controller with 2-Position Source Selector and Volume Control; US Version (Black) For use with CSM-21, CSM-32	\$	80.00
JBLCSR2SVWHTV	CSR-2SV-WHT	Wall Controller with 2-Position Source Selector and Volume Control; US Version (White) For use with CSM-21, CSM-32	\$	80.00
JBLCSR3SVBLKV	CSR-3SV-BLK	Controller with 3-Position Source Selector and Volume Control; US Version (Black) For use with CSM-32	\$	80.00
JBLCSR3SVWHTV	CSR-3SV-WHT	Wall Controller with 3-Position Source Selector and Volume Control; US Version (White) For use with CSM-32	\$	80.00
JBLCSRVBKV	CSR-V-BLK	Wall Controller with Volume Control; US Version (Black) For use with CSM-21, CSM-32, All CSMA	\$	80.00
JBLCSRVWHTV	CSR-V-WHT	Wall Controller with Volume Control; US Version (White) For use with CSM-21, CSM-32, All CSMA	\$	80.00
CSS8004	S/M, CSS8004 - 4", 5W	4" Commercial Series Ceiling Speaker. 90 dB sens, 5W multi-tap for 100V/70V 25V, pre-assembled with driver/grille/transformer, 175 deg coverage; punched metal grille, compatible with CSS-BB4 backcan and CSS-TB4/8 tile rails (priced as each; sold individually; master packs are 6 pcs).	\$	23.00
CSS8008	S/M, CSS8008 8", 5w	8" Commercial Series Ceiling Speaker. 96 dB sens, 5W multi-tap for 100V/70V 25V, pre-assembled with driver/grille/transformer, 120 deg coverage; punched metal grille, compatible with CSS-BB8 backcan and CSS-TB4/8 tile rails (priced as each; sold individually; master packs are 6 pcs).	\$	31.00
CSS8018	S/M, CSS8018 8", 10W	8" Commercial Series Ceiling Speaker. Very high 97 dB sens, 10W multi-tap for 100V/70V 25V, pre-assembled with driver/grille/transformer, 110 deg coverage; punched metal grille, compatible with CSS-BB8 backcan and CSS-TB4/8 tile rails (priced as each; sold individually; master packs are 6 pcs).	\$	42.00
CSS-BB4X6	S/M, CSS-BB4X6-- 4" BAC	Pack of 6 pcs of 4" backcans for CSS8004. Steel, zinc-plated, powder-coated, 4.8" (121mm) deep, 5 knockouts (priced an sold as a pack of 6 pcs).	\$	59.00
CSS-BB8X6	CSS-BB8X6 8" BACKCAN (Pack of 6 pcs of 8" backcans for CSS8008 or CSS8018. Steel, zinc-plated, powder-coated, 4.8" (121 mm) deep, 5 knockouts (priced an sold as a pack of 6 pcs).	\$	109.00
CSS-TR4/8x12	CSS-TR4/8x12	Pack of 12 pcs Tile Rails for CSS-BB4 and CSS-BB8 Backcans (Priced as package)	\$	34.00

Lay-in Ceiling Tile Speaker, 8" driver, for US-size suspended grid ceilings (NOT for 600 x 600 mm metric grids), combined 70V/100V and low impedance direct operation, 20W at 8Ω, 10W multi-tap transformer with taps at 10W, 5W, 2.5W (and 1.3W for 70V only) via rotary tap-selector switch, max SPL of 108 (peaks of 114 dB) @ 1m (low-Z), very low-profile at 103 mm (4.1") deep, bare-wire connection in protected compartment, very high 96 dB sensitivity, 100° conical coverage pattern, designed for high intelligibility, UL1480 and UL2043, white full-face grille. Sold as each; packed in pairs.

LCT 81C/T	Low-Profile Lay-In 2' x 2' (\$	130.00
		Compact 2-Way 100V/70V/8Ω Surface-Mount Loudspeaker. 5¼" LF and ¾" HF, 85 Hz – 18 kHz, 10 Watt Multi-Tap Transformer for 100V or 70V Distributed Speaker Lines (10W and 5W taps, plus 2.5W at 70V only), or 60W at 8Ω, ball-type wall-mount included. (priced as each; sold in pairs). 5¼" LF and ¾" HF, 85 Hz – 18 kHz, 10 Watt Multi-Tap Transformer for 100V or 70V Distributed Speaker Lines (10W and 5W taps, plus 2.5W at 70V only), or 60W at 8Ω, ball-type wall-mount included. (priced as		
CSS-1S/T	2-way Surface-Mount Speaker each; sold in	Compact 2-Way	\$	130.00
CSS-H15	15 Watt Paging Horn (6 in	15 Watt Paging Horn. (Priced as each, 6 in masterpack)	\$	95.00
CSS-H30	30 Watt Paging Horn (4 in	30 Watt Paging Horn (Priced as each, 4 in masterpack)	\$	130.00